## LED LUMINAIRES TECHNICAL SPECIFICATION SHEET



Tel: 01252 311016 Email: sales@daxlite.com Web: www.daxlite.com



## Product: 40W Slim Profile LED Batten Product Code: DXBAT120DL / DXBAT120CW ISSUE A, 08.06.2016

GENERAL DETAILS	
Description	4 Ft Low Profile LED Batten
Overall Dimensions (mm)	1200mm (Length) x 75mm (Width) x 23mm (Depth)
Finishes Available	Aluminium Base with White Opal Polycarbonate Diffuser
Product Weight	0.56 kg
Energy Rating	A
Ingress Protection	IP20
LIGHT SOURCE	
Rated Wattage	40 Watts +/- 5%
Lumens	3800 lumens / 3700 lumens
Lumens per Watt	95 lumens per watt / 93 lumens per watt
Recommended Product Location	Commercial office ceilings, schools and retail sector
Light Source (type)	SMD - LED
Colour Temperature (K) Kelvin	6000K Daylight White / 4000K Cool White
Colour Rendering Index CRI: Ra	CRI: Ra >80
Light Source Life (Hrs)	Average Life: 30,000 Hrs
Beam Angle	120°
ELECTRICAL	
Voltage (V)	220 - 240V. 50 Hz. AC
Running Current (I)	0.18 Amps @ 220V
Total Running Wattage (W)	40W
Dimmable	No
Control Gear	Integrated Driver
Power Factor Correction (PFC)	0.95
Electrical Classification	Class II
Cabling (Electrical connections)	Prewired cable
INSTALLATION	
Distance from illuminated object	0.5m
Socket / Fixture	Surface Mounted. Suspension (requires add accessories)
Recommended Working Temperature	Min -10°C to Max +40°C
MATERIALS	
Main Housing (Material)	Aluminium base
Front Shield (Material)	Polycarbonate Opal
APPROVALS	
Guarantee	3 Years (from date of purchase)
Certificate of Conformity	CE (LVD & EMC)
Manufactured in accordance to:	RoHS, LM-80, IES/LDT

DaxLite reserves the right to withdraw, improve or modify any design without prior notification. DaxLite cannot be held responsible for the incorrect application of any product. Company Registration Number: 7955361 VAT Number: 134182827