GROUND LIGHTS TECHNICAL SPECIFICATION SHEET



Email: sales@daxlite.com Web: www.daxlite.com



Product: IP68 12V LED DECKING LIGHT

Product Code: DXGLO16 ISSUE A, 24.03.17

	1330E A, 4
GENERAL DETAILS	
Description	12V LED Aluminium Rescessed Decking Light
Overall Dimensions (mm)	Rim Dia: 60mm, 43mm Height, 50mm Cut Out
Finishes Available	Satin Silver bezel, Stainless Steel Construction
Product Weight	0.42 kg
Ingress Protection	IP68
LIGHT SOURCE	
Rated Wattage	1 Watts
Lumens	116lm
Lumens per Watt	116lm
Recommended Product Location	Outdoor
Light Source Brand	Modalight
Colour Temperature (K) Kelvin	4000K
Colour Rendering Index CRI: Ra	85
Light Source Life (Hrs)	30,000
Beam Angle	20
Light Source Working Temperature (Celcius)	32
ELECTRICAL	
Voltage (V)	12V
Running Current (V)	12V
Total Running Wattage (W)	1W Max
Electrical Classification	Class I
Power Factor Correction (PFC)	
Cabling (Electrical Connections)	1m rubberised cable, to be wired in series
INSTALLATION	
Distance from illuminated object	0.5m
Method of Fix	Recessed in ground
Recommended Working Temperature	Max +35°C
MATERIALS	
Main Housing (Material)	Marine Grade Aluminium
Front Shield (Material)	Toughened Glass with Brushed Aluminium Bezel
APPROVALS	

Guarantee	1 Years (from date of purchase)
Quality Assurance System	ISO9001:2008
Certification	CE
Manufactured in accordance to:	BSEN 60 598 -2-1