

CDPW self-priming centrifugal pumps are direct replacement for one of the most popular pumps sold to industrial and municipal customers. We have used these replacement designs for over 30 years on our diesel powered trash pumps.

All pumps assembled in the USA – 100% tested prior to shipment to assure the highest quality to published performance. **1yr warranty on parts and craftsmanship.**

- Heavy duty cast iron construction
- Balanced 2 vane non-clog impeller
- 3" spherical solids passing
- Oil lubricated Tungsten Carbide / Tungsten Carbide / Viton shaft seal
- Shaft sleeve standard on all units
- Cast iron or Stainless Steel wear plate
- Easily accessible clean out cover, back pull-out for easy maintenance
- Double row oil lubricated ball bearings, min. B10 life 25,000 hours



CDPW Model	TH4	TH6
Direct replacement for Marlow	M4DTH24EL	M6ETH28EL
Suction / Discharge	125# 4" flanged	125# 6" flanged
Max. Flow Rate @ 1750 rpm	750 gpm	1,500 gpm
Max. TDH @ 1750 rpm	97 ft. shutoff	125 ft. shutoff
Max. Working Pressure	85 psi	85 psi
Max. Horsepower	20 @ 1,750 rpm	45 @ 1,750 rpm
Max. Speed	2,400 rpm	1,750 rpm
Overall Size L x W x H (inches)	40.1 x 16.5 x 27.1	42.7 x 19.8 x 28.6
Dry Weight (pounds)	580 lbs.	675 lbs.

Rebuild Kits: Complete rebuild kit includes 2 high double row bearings, shaft seal, wear plate, all gaskets, o-rings and instructions. Specify model when ordering.

Repair parts are not made by ITT-Goulds Marlow®. All CDPW Inc. components are quality aftermarket parts that interchange with the original. ITT-Goulds Marlow Trash Hog® are registered trademarks of ITT MANUFACTURING ENTERPRISES, LLC WILMINGTON, DELAWARE.

