

No system is complete without proper pump fittings and hoses to provide a fast, positive and leak proof connections. From camlock to Bauer type, high or low pressure, CDPW will provide a system suitable for your application.



Consult factory for Bauer & Dresser fittings

Item #	Description	4"	6"	8"
1.	Blue Lay-Flat Discharge, cam-lock coupled 50'	LFB-4-50	LFB-6-50	LFB-8-50
	Blue Lay-Flat Discharge, uncoupled per foot	LFB-4	LFB-6	LFB-8
	Red Lay-Flat Discharge, cam-lock coupled 50'	LFR-4-50	LFR-6-50	LFR-8-50
	Red Lay-Flat Discharge, uncoupled per foot	LFR-4	LFR-6	LFR-8
2.	Suction Hose, female cam lock x king nipple, 20'	SHA-4	SHA-6	SHA-8
	Suction Hose, male x female cam lock, 20'	SHB-4	SHB-6	SHB-8
	Suction Hose, uncoupled per foot	SH-4	SH-6	SH-8
3.	Aluminum Cam-Lock, female "C" x hose barb	CL-C4	CL-C6	CL-C8
	Aluminum Cam-Lock, male "E" x hose barb	CL-E4	CL-E6	CL-E8
4.	Steel King Nipple, male threaded x hose barb	KN-4	KN-6	KN-8
5.	Foot Valve	FV-4	FV-6	FV-8
6.	Large (square) Hole Strainer	SSQ-4	SSQ-6	SSQ-8
7.	Small Hole Strainer	SRD-4	SRD-6	SRD-8

Item #	Description	1 ½"	2 ½"
8.	Jet Hose, brass NPT threaded coupling male x female 50'	JH-15-50	JH-25-50
	Jet Hose, brass NPT threaded coupling male x female 100'	JH-15-100	JH-25-100

**“The finest dewatering pumps and wellpoint equipment since 1923”**