

Complete Dewatering now carries two of the most popular types of wellpoint systems. Our traditional style with 2" wellpoints, rigid plastic saddles, and O-ring sealing swing joint elbows, or the rubber grommet type system, with a contoured header grommet insert and welltop insert designed around the 1 1/2" wellpoint.

## Complete Type System:

**Header Pipe** – 6", 8", 10" header pipe  
7 saddles per 20' section



**Swing Joint Assy.** – O-ring sealing elbows with valve. Designed for 2" wellpoints and our rigid header saddle.



**2" PVC Wellpoint** – large size for faster dewatering and inner draw down tube for maximum water drawdown.

**Replacement Header Saddles** – specify for 6", 8", or 10" header pipe



**Hat Plug** – Seals unused header saddles



## Grommet Type System:

**Header Grommet Insert** – can be used with any sch. 40 PVC pipe from 4" to 12"



**Welltop Grommet Insert** – fits 1 1/2" PVC coupling (welltop)



**Grommet Plug** – seals unused grommet inserts

**1 1/2" PVC Wellpoint** – compact design ideal for small dewatering projects.



**Tapered Elbow Swing Joint Assy.** – tapered ends fit into the rubber grommets, expanding the grommets for an airtight fit in the header and wellpoint.



## Common to either type system:

**Rubber Molded Header Pipe Connector Sleeves** – Molded sleeves with a tapered ID fit quickly onto the header pipe.



**QD "Quick Disconnect" Stainless Steel Header Clamps** – for 6", 8", 10" header pipe. Flip-up tensioning screw allows you to pull the end of the band through the screw quickly.



**Steel or PVC Header Fittings** – 4", 6", 8", 10" Tee; 90°, 45°, 22.5° Elbows; Wye; End Cap



**Wellpoint Clay** – seals small leaks in the wellpoint system, header pipe, swings, pumps, etc. Doesn't dry up like plumbers putty, not messy like pipe compound.



**Dresser Bolt-on Couplings** – 4" through 12" Connects PVC discharge pipe securely to the pump, preventing discharge pipe blowout that can underwash your pump.



**Steel Self Jetting Wellpoints** – 3' section with 2" PVC screen, jet head, and 1 1/2" connection for your steel riser pipe. Used with either the Complete O-ring type or grommet type systems.



**Aluminum Welltop** – Used with the steel self jetting wellpoint, connects to the top of the 1 1/2" steel riser pipe. Now available to fit the Complete O-ring sealing swing joint or the rubber welltop grommet system.



*This is just a partial list of the wellpoint equipment we offer. Other components include: Jet rods (stinger), steel punches, steel jet casings, jetting hose, suction and discharge hoses, header jacks, swing joint mops, Call Complete for any wellpoint equipment and pump needs.*