

Since 1923 Complete Dewatering has been providing general contractors, utility contractors, and municipal industries with the finest dewatering pumps and equipment. Below is a partial listing of the products we offer. If you don't see what you're looking for, please call.

Trash Pumps

Self priming centrifugal trash pumps, 4", 6", 8", 10" or 12" sizes; capacities to 6,000 gpm. Wheel or frame mount. Optional vacuum assist system for 4" to 8" models for rapid priming and re-priming. Suited for open sumping, sewer bypass and construction dewatering.

By-Pass Pumps

Our most versatile pump. 6" discharge, 6" or 8" suction, flow rate to 2,250 gpm, heads to 130', 3" solids passing. For open sumping, sock drain, wellpointing or bypass pumping.

Wellpoint Pumps – Centrifugal or Rotary

Vacuum assisted wellpoint pumps in 4", 6", 8" and 10" sizes, diesel or electric powered, frame or wheel mount. Rotary lobe vane pumps from 4" to 8", diesel or electric.

Submersible Pumps – Deep Well or SlimLine

Complete submersible pump systems for dewatering >25' below surface. Up to 50 Hp.

Wellpoint Equipment

PVC header pipe in 6", 8" and 10" sizes, rigid plastic saddles or rubber grommet style
PVC wellpoints, 2" or 1 ½"
Steel self-jetting wellpoints
Swing joint assembly, o-ring or rubber grommet style
Rubber header sleeves
Quick disconnect screw clamps
Steel or PVC header elbows, tees, caps
Hat plugs, Wellpoint clay

Jetting Equipment

High pressure jetting pumps
High pressure jetting hoses
Steel or aluminum jet rods
Sand casings, steel punches

Hoses

Rubber suction hose
PVC suction hose
Lay flat discharge hose
Cam lock couplings
Latch and ring type couplings

Pump Parts

Complete
Berkeley
Cornell
Pentair
Gorman Rupp
ITT-Goulds
Masport

Engine Parts

John Deere
Deutz
Perkins
Kohler
Hatz

Instrument & Control Panels

Murphy
North American Electric Controls
Auto start systems for diesel engines (new pump option or existing pump retrofit package)

"The finest dewatering pumps and wellpoint equipment since 1923"