



966 – 77<sup>th</sup> Avenue, Oakland, CA 94621  
Phone: 510-635-2736 Fax: 510-635-2738  
www.thermalpoolcover.com

## Handling “EnergySaver”® Pool Covers

1. Before unpacking cover(s), please note panel size and number written on the packaging material that would suggest where to place the individual cover relative to the size and configuration of the pool. Be careful not to cut covers inside when attempting to open packages.

*Important:* Look for signs of **FREIGHT DAMAGE**.

If one is found, DO NOT OPEN the package, call the freight company for inspection.

2. After discarding all packing materials, attach a tow-rope onto the center pull-point of the leading edge of cover and place cover in the pool (hint: pulling cover in the water means less abrasion). Pool covers shipped from the factory rolled lengthwise. By slowly pulling on the attached tow-rope from across the pool and unrolling the cover at other end of the pool, two person can unfurl the cover. Let the cover glide on the water surface. Beware of broken/jagged lane lines that may cause heavy abrasion and premature tear on the cover.

*Important:* Pulling cover too fast will cause the leading edge to dive and hard to pull and also create a **DANGEROUS** situation for personnel at other end.

3. Once cover is fully unrolled, grab the corner pull-point (note: corner pull-point is the strongest) and properly position cover on the pool. Do not overlap covers. Overlapped covers are susceptible to wind.

4. Make sure all “Warning” labels are clearly legible and visible from the deck and around the perimeter of the pool.

*Important:* Call T-Star for missing or torn “Warning” labels.

For **SAFETY**, labels must be legible and securely attached to all covers at all times.

5. When retrieving covers off the pool for storage, please pull from one of the corner pull-point and then move on toward the center of the cover and hook up the dowel to the center tab on the reel. Avoid folding and creasing covers by connecting all available dowels to the reel tabs.

6. Prevent abrasion by rolling cover(s) evenly onto the reel, avoiding ‘telescopic’ effect. Secure it by attaching cordage around the rolled-up covers.

7. Once all covers are safely stored on the reel, be sure to use a protective cover to shield it from harmful Ultra Violet exposures. Note: our warranty requires the regular use of protective materials for all covers stored on the reels.

8. Repeat process # 2, 3, and 4 when deploying covers onto the pool.