



DURASOL

50

VINYL ACRYLIC
FLAT

DESCRIPTION:

Durasol 50 flat has outstanding hide, durability, adhesion, color retention, and leveling.

Durasol 50 flat is an excellent choice for ceiling's, interior walls, or anywhere a durable flat finish is required

COLORS

Durasol 50 can be made in any color

PACKAGING

Gallon cans, and 5 gallon pails

FINISH

Flat

SURFACES

Properly primed and prepped wood, drywall, stucco, and masonry.

DRY TIME

To touch – 30 Minutes

To recoat – 2 to 4 hours

COVERAGE

300 to 400 sq. ft. per gallon depending on surface texture and porosity

APPLICATION

Durasol 50 may be applied by brush, roller, or spay equipment.

THINNING

Durasol 50 is ready to use out of the can when thinning is required use a small amount of water

CLEAN-UP soap and warm water cleanup

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, or mildew, chalk, loose peeling paint or any other contaminants. For best results two coats are recommended one prime and one finish. New unpainted surfaces should be properly primed with a specified primer.

QCX3

THE TRIPLE CHECK GAURANTEE

PaintSolutions a division of inksolutions 5928 Garfield Ave. Commerce, C.A. 90040

(P) 323-726-8100 (F) 323-622-1760

WWW.PAINTSOLUTIONS.US