



PERMASOL 250

VINYL ACRYLIC FLAT

DESCRIPTION:

PaintSolutions Permasol 250 is a premium flat that has outstanding hide, durability, adhesion, color retention, and leveling.

Permasol 250 is an excellent choice for interior walls, plaster, masonry, concrete or anywhere else a durable flat finish is required.

COLORS

Permasol 250 can be made in any color

PACKAGING

Gallon cans, and 5 gallon pails

FINISH

Flat

SURFACES

Properly primed and prepped wood, drywall, stucco, and masonry

DRY TIME

To touch – 30 Minutes

To recoat – 2 to 4 hours

COVERAGE

300 to 400 sq. ft. per gallon depending on surface texture and porosity

APPLICATION

Permasol 250 may be applied by brush, roller, or spray equipment.

THINNING

Permasol 250 is ready to use out of the can if thinning is required use small amount of water

CLEAN-UP soap and warm water cleanup

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, or mildew, chalk, loose peeling paint or any other contaminants. For best results two coats are recommended one prime and one finish. New unpainted surfaces should be properly primed with a specified primer.

QCX3

THE TRIPLE CHECK GAURANTEE

PaintSolutions a division of inksolutions 5928 Garfield Ave. Commerce, C.A. 90040

(P) 323-726-8100 (F) 323-622-1760

WWW.PAINTSOLUTIONS.US