



DURASOL

25

VINYL ACRYLIC FLAT

DESCRIPTION:

Durasol 25 flat has outstanding hide, durability, adhesion, color retention, and leveling.

Durasol 25 flat is an excellent choice for ceilings, maintenance, or anywhere a durable flat finish is required.

COLORS

Durasol 25 can be made in any color

APPLICATION

Durasol25 may be applied by brush, roller, or spay equipment.

PACKAGING

Gallon cans, and 5 gallon pails

THINNING

Durasol 25 is ready to use out of the can when thinning is required use a small amount of water

FINISH

Flat

CLEAN-UP soap and warm water cleanup

SURFACES

Properly primed and prepped wood, drywall, stucco, and masonry.

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, or mildew, chalk, loose peeling paint or any other contaminants. For best results two coats are recommended one prime and one finish. New unpainted surfaces should be properly primed with a specified primer.

DRY TIME

To touch-30 Minutes temperature at 50-90 degrees.
To recoat-2 to 4 hours

COVERAGE

300 to 400 sq. ft. per gallon depending on surface texture and porosity

QCX3

THE TRIPLE CHECK GAURANTEE

PaintSolutions a division of inksolutions 5928 Garfield Ave. Commerce, C.A. 90040

(P) 323-726-8100 (F) 323-622-1760

WWW.PAINTSOLUTIONS.US