



## SYNKOLOID

### 100

#### INTERIOR SPACKLING PASTE

**DESCRIPTION:** A ready to use quick, easy, invisible patch. This long lasting and easy to apply paste dries hard and feathers to an unnoticeable edge with minimum shrinkage.

**SYNKOLOID 100:** is recommended for interior resurfacing and filling: holes, breaks, and cracks in interior walls; filling recessed (primed) nail holes in moldings, doors and window frames

**COLORS**

Wet - White

Dry - Off-White

**Tinting:** Can be tinted with universal colorants, up to 2 ounces per gallon.

**PACKAGING:**

Gallons, Quarts and 9oz

**CLEAN UP:** Soap and warm water.

**DRY TIME:**

Normal repair - Less than an hour.

Deep repair - May take longer, based on depth.

**MIXING:** None required.

Ready to use from the container.

**FREEZE - THAW:** Do not Freeze.

**FEDERAL SPECIFICATION:** Meets SS-P-004550.A  
Type II

**CAUTIONS:** Keep out of the reach of children.  
Do not take internally. Use with adequate ventilation.  
Contains no: asbestos, lead or mercury.  
Wear a dust mask when sanding.

**APPLICATION**

Apply with a putty knife. Press firmly into place. Deep fills should be patched in two or more applications, allowing the compound to dry in between fills.

Do not apply when temperature is below 50F.

**VISCOCITY:** Paste Consistency.

**SURFACES**

Prime surfaces to improve adhesion. Priming is recommended before top coating with sheen or gloss paints to improve uniformity

**SURFACE PREPARATION**

All surfaces must be free of dirt, grease, wax, mildew, chalk, mold, loose peeling paint or any other contaminants. Rotted wood should be removed before spackling. Rusting metal and other questionable surfaces should be primed before spackling.

**QCX3**  
**THE TRIPLE CHECK**  
**GUARANTEE**

PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040  
(P) 323-726-8100 (F) 323-622-1760  
[WWW.PAINTSOLUTIONS.US](http://WWW.PAINTSOLUTIONS.US)