



SYNKOLOID

120

EXTERIOR SPACKLING PASTE

DESCRIPTION: A ready to use, professional spackling compound for patching and repairing exterior surfaces not subject to abnormal expansion or contraction. Its unique formula offers a buttery consistency, with easy application, minimum shrinkage, and outstanding adhesion to difficult surfaces.

SYNKOLOID 120: Fills cracks, voids, holes, dents, and nail head (primed). Recommended for application on wood, plywood, particleboard, masonry, stucco, shingles and primed metal.

COLORS

Wet - White

Dry - Off-White

Tinting: Can be tinted with universal colorants, up to 2 ounces per gallon.

PACKAGING:

Gallons, Quarts and Pint.

CLEAN UP: Soap and warm water.

DRY TIME:

Normal repair - Less than an hour.

Deep repair - May take longer, based on depth.

MIXING: None required.

Ready to use from the container.

FREEZE - THAW: Do not Freeze.

FEDERAL SPECIFICATION: Meets SS-P-00450-A
Type II

CAUTIONS: Keep out of the reach of children.
Do not take internally. Use with adequate ventilation.
Contains no: asbestos, lead or mercury.
Wear a dust mask when sanding.

APPLICATION

Apply with a putty knife. Press firmly into place. Deep fills should be patched in two or more applications, allowing the compound to dry in between fills.

Do not apply when temperature is below 50F.

VISCOSITY: Paste Consistency.

SURFACES

Prime surfaces to improve adhesion. Priming is recommended before top coating with sheen or gloss paints to improve uniformity

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, mildew, chalk, mold, loose peeling paint or any other contaminants. Rotted wood should be removed before spackling. Rusting metal and other questionable surfaces should be primed before spackling.

QCX3
THE TRIPLE CHECK
GUARANTEE

PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040
(P) 323-726-8100 (F) 323-622-1760
WWW.PAINTSOLUTIONS.US