



SYNKOLOID

280

TEXTURED TUFF-PATCH

DESCRIPTION: This is a textured, ready, tough but still flexible, vinyl-based patching compound for interior / exterior use.

SYNKOLOID TEXTURED TUFF-PATCH: Recommended for patching and resurfacing all types of material including: masonry, wood, firewalls, brick and metal. Allows slight structural movement without loosening adhesion and/or patch integrity with age.

COLORS

Off-White

Tinting: Can be tinted with universal colorants, but may be difficult due to textured paste.

PACKAGING:

Gallons & Quarts.

CLEAN UP: Soap and warm water, prior to drying. If dried, use lacquer thinner.

DRY TIME:

Overnight when application is less than 1/8" thick. Thicker films, higher humidity or lower temperature may prolong dry time.

MIXING: None required. Ready to use from the container.

FREEZE – THAW: Do not Freeze.

FEDERAL SPECIFICATION: None

CAUTIONS: Keep out of the reach of children. Do not take internally. Use with adequate ventilation. Contains no: asbestos, lead or mercury. Wear a dust mask when sanding.

APPLICATION

Apply with a putty/broad knife or trowel. May be applied to damp surfaces. Thoroughly dry before top coating. To blend patch with the surrounding textured surface, stipple gently with a worn, stubby brush as needed, while still soft.

VISCOCITY: 6,000 + 400 Poises.

DURABILITY:

Will not brittle with age.

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, mildew, chalk, mold, loose peeling paint or any other contaminants. Rotted wood should be removed before spackling. Rusting metal and other questionable surfaces should be primed before patching.

QCX3

**THE TRIPLE CHECK
GUARANTEE**

**PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040
(P) 323-726-8100 (F) 323-622-1760
WWW.PAINTSOLUTIONS.US**