



## **SYNKOLOID**

**300**

### **SMOOTH - TUFF-PATCH**

**DESCRIPTION:** This is a textured, ready, tough but still flexible, vinyl-based patching compound for interior and primed exterior use.

**SYNKOLOID TEXTURED TUFF-PATCH:** Recommended for patching and resurfacing all types of material including: masonry, wood, roofing, brick, metal, firewalls, flashing, gutters, decks, stucco, non-glazed tile, trailer tops, skylights, chimneys and vents. Allows slight structural movement without loosening adhesion and/or patch integrity with age.

**COLORS**

Off-White

**Tinting:** Can be tinted with universal colorants, but may be difficult due to paste consistency.

**PACKAGING:**

Gallons & Quarts.

**CLEAN UP:** Soap and warm water, prior to drying. If dried, use lacquer thinner.

**DRY TIME:**

Overnight when application is less than 1/8" thick. Thicker films, higher humidity or lower temperature may prolong dry time.

**MIXING:** None required. Ready to use from the container.

**FREEZE - THAW:** Do not Freeze.

**FEDERAL SPECIFICATION:** None

**CAUTIONS:** Keep out of the reach of children. Do not take internally. Use with adequate ventilation. Contains no: asbestos, lead or mercury. Wear a dust mask when sanding.

**APPLICATION**

Fill holes or cracks using putty knife. Deep cracks may require additional fillings. Tuff-Patch is not meant to be sanded. May be primed and painted when dry. Not recommended for underwater use.

**VISCOSITY:** 45,000 + 1,000 Poises.

**DURABILITY:**

Will not brittle with age.

**SURFACE PREPARATION**

All surfaces must be clean. Remove all dirt, dust, oil and grease before applying. Dull glossy surfaces by light sanding.

**QCX3**  
**THE TRIPLE CHECK**  
**GUARANTEE**

**PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040**

**(P) 323-726-8100 (F) 323-622-1760**

**WWW.PAINTSOLUTIONS.US**