



SYNKOLOID 940 LATEX WOOD FILLER

DESCRIPTION: SNYKO Latex Wood Filler is modeled after real wood. This filler takes stain beautifully, can be sanded smooth, hold nails and screws, can be drilled, sawed and planed.

SYNKOLOID TEXTURED TUFF-PATCH: Besides providing a permanent, neutral-colored filler for cracks, chips and holes in: wood, metal, glass or stoned surfaces. This filler can be used to set loose joints, handles and knobs in furniture, reset nails and screws which have worked loose and repair damaged surfaces such as paneling, moldig, plywood and other interior wood surfaces

COLORS

Off-White

Tinting: Can be tinted with universal colorants, but may be difficult due to paste consistency.

PACKAGING:

Gallons & Quarts.

CLEAN UP: Soap and warm water, prior to drying. If dried, use lacquer thinner.

DRY TIME:

Overnight when application is less than 1/8" thick. Thicker films, higher humidity or lower temperature may prolong dry time.

MIXING: None required. Ready to use from the container.

FREEZE - THAW: Do not Freeze.

FEDERAL SPECIFICATION: None

CAUTIONS: Keep out of the reach of children. Do not take internally. Use with adequate ventilation. Contains no: asbestos, lead or mercury. Wear a dust mask when sanding.

APPLICATION

Fill holes or cracks using putty knife. Deep cracks may require additional fillings. Tuff-Patch is not meant to be sanded. May be primed and painted when dry. Not recommended for underwater use.

VISCOCITY: 45,000 + 1,000 Poises.

DURABILITY:

Will not brittle with age.

SURFACE PREPARATION

All surfaces must be clean. Remove all dirt, dust, oil and grease before applying. Dull glossy surfaces by light sanding.

QCX3
THE TRIPLE CHECK
GUARANTEE

PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040
(P) 323-726-8100 (F) 323-622-1760
WWW.PAINTSOLUTIONS.US