



CEM-BOND 500 SERIES FLOOR & PATIO PAINT

DESCRIPTION:

CEM-BOND is an Interior/Exterior 100% acrylic floor and patio paint. The durable latex film dries to a soft low sheen finish and may be walked on in 24 hours, depending on drying conditions.

RECOMMENDATION: Inside or outside on new or old wood and masonry surfaces such as patios, cellar floors, playrooms and porches. Cem-Bond is not recommended for concrete floors or other surfaces which vehicles are parked.

COLORS

CEM-BOND is available in 8 standard colors. There is also a tint/base system available.

PACKAGING

Gallon cans, and 5 gallon pails

FINISH

Low Sheen

SURFACES

Asphalt, concrete, brick, wood

DRY TIME

To touch – 30 Minutes
Walked on in 24 Hours

COVERAGE

300 to 400 sq. ft. per gallon depending on surface texture and porosity

APPLICATION

Brush: Synthetic or nylon bristled brush
Roller: 1/4" nap or smooth surface to 3/8" to 1/2:" nap for rough surfaces.

APPLICATION TEMPERATURE

55-100-degree F.

THINNING

CEM-BOND is ready to use out of the can if thinning is required use small amount of water

CLEAN-UP soap and warm water cleanup

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, Or mildew, chalk, loose peeling paint or any other contaminants. For best results two coats are recommended one prime and one finish. New unpainted surfaces should be properly primed with a specified primer.

QCX3

THE TRIPLE CHECK GUARANTEE

PaintSolutions a division of Inksolutions 5928 Garfield Ave. Commerce, C.A. 90040
(P) 323-726-8100 (F) 323-622-1760
WWW.PAINTSOLUTIONS.US