



SYNKO

PRIME-RITE TOTAL PRIME 456 INTERIOR / EXTERIOR

DESCRIPTION:

PRIME-RITE TOTAL PRIME 456 is a water based primer for general purpose use for most application. Seals stains, graffiti and tannin bleed. Has superior adhesion to all surfaces, including metal. Total-Prime 456 is low odor, dries fast with exceptional flow and leveling

DESCRIPTION

A water based low odor clear sealer.

PACKAGING

Gallon cans, and 5 gallon pails

FINISH

Glossy sheen

SURFACES

Complete Seal 650 can be used on stucco, masonry and dry wall. It is ideal for restoring torn damaged drywall and will seal chalky porous surfaces. Use on new drywall as a prep coat or size prior to wallpapering.

DRY TIME

To touch – 30 Minutes

COVERAGE

400 to 600 sq. ft. per gallon depending on the surface texture and porosity

APPLICATION

May be applied with roller, brush or spray. Do not shake, stir lightly.

THINNING

Ready to use. If thinning is desired use clean water.

CLEAN-UP

Soap and warm water cleanup

SURFACE PREPARATION

All surfaces must be free of dirt, grease, wax, or mildew, loose peeling paint or any other contaminants. For extremely chalky surfaces spot check for desired results

Ideal for interior or exterior surfaces.

QCX3

THE TRIPLE CHECK GUARANTEE