

Optical Launch Jumper



Standard Features

Durable, convenient, compact and light weight

Multimode (50 μ m / 62.5 μ m) and single-mode fibers available

6 ft (2 m) jumper leads allow easy access between OTDR and patch panel

Optional connector cleaning stick available **See connector cleaning stick spec sheet*

3C Dynamics Optical Launch Jumpers are designed with the technician in mind. A carabiner is included to provide the ability to conveniently and securely hang the unit on an equipment rack or on the technicians belt while in use. Each jumper test lead is easily accessed and provides ample work length between the OTDR and the tested fiber.

Jumper test leads are quickly rolled up and placed in a ruggedized bag to prevent test lead/connector damage and provide water resistance during storage.

Optional connector cleaning products maximize testing results and store easily inside bag with test leads.

Custom bag designs are available upon request allowing specialized company colors, designs and logos.



Optical Launch Jumper



Specifications

Standard Jumper Lengths	Test Lead Length (each)	Approximate Dimensions (H x W x D)	Estimated Weight	Operating Temperature
50 to 500 m (164 to 1640) ft	6 ft (1.82 m)	5.8 x 10.5 x 1.0 in (14.7 x 26.9 x 2.5) cm	2 lb (0.9 kg)	0° to 140°F (-20° to +140°)C

Ordering Information

OLJ -

1
 2 3 4 5 6

- | | | |
|--|---|---|
| <p>1 Select Total Fiber Length (50 – 500) meters</p> <p>Example:
050 = 50 meters
500 = 500 meters</p> | <p>3 Select Connector One</p> <p>Multimode
A = LC
B = SC
C = ST Compatible</p> | <p>5 Select Connector Two</p> <p>Multimode
A = LC
B = SC
C = ST Compatible</p> |
| <p>2 Select Fiber Type</p> <p>Multimode
3 = 50µm (OM2) *
4 = 62.5µm (OM1)</p> <p>Single-mode
S = Single-mode (OS2)
N = NZDSF</p> <p><small>*OM2 is compatible with OM3 and OM4 during OTDR operations.</small></p> <p><small>** Custom quotes available based on design and volume.</small></p> | <p>Single-mode
F = LCUPC
G = LCAPC
H = SCUPC
J = SCAPC
K = FCUPC
L = FCAPC
P = Optitap®</p> | <p>Single-mode
F = LCUPC
G = LCAPC
H = SCUPC
J = SCAPC
K = FCUPC
L = FCAPC
P = Optitap®</p> |
| | <p>4 Connector One Cleaning Stick</p> <p>1 = Include
0 = Do not include</p> | <p>6 Connector Two Cleaning Stick</p> <p>1 = Include
0 = Do not include</p> |