

Connector Adapters



Standard Features

Industry standard adapters that can be used for patch panel replacement or by the technician/installer during testing and referencing test jumpers.

All adapters come with ceramic alignment sleeves.

3C Dynamics adapters compliment their other test fiber products. Standard connector types are SC, ST, FC, and LC in both single-mode and multimode.

Hybrid adapters available upon request.

Specifications

Adapter insertion loss is dependent upon the connectors used. 3C Dynamics adapters are tested to ensure they provide < 0.4 dB insertion loss with known good connectors. Operating temperatures are - 40° C to 75° C. Durability is industry compliant.

Ordering Information

Part Number	Adapter	Fiber Type
AD-SCU-SCU	SCUPC - SCUPC	Singlemode
AD-SCA-SCA	SCAPC - SCAPC	Singlemode
AD-LCU-LCU	LCUPC - LCUPC	Singlemode
AD-LCA-LCA	LCAPC - LCAPC	Singlemode
AD-FCS-FCS	FC - FC	Singlemode
AD-STS-STS	ST - ST	Singlemode
AD-SCP-SCP	SC - SC	Multimode
AD-LCP-LCP	LC - LC	Multimode
AD-FCP-FCP	FC - FC	Multimode
AD-STP-STP	ST - ST	Multimode

