

CLP 674 pumps

CLP-140 - CLP-500

High flow - G frame (not available for subsea applications)

Type	Flow l/min. [gpm]		Pump power	Pump torque		Discharge pressure	MAWP
	Min.	Max.	kW [hp]	Min. Nm	Max. Nm	Min. barg [psig]	barg [psig]
CLP-140	86.27 [22.79]	187.34 [49.49]	65.77 [88.20]	21.00	419.00	10 [145]	100 [1450]
CLP-185	112.35 [29.68]	243.97 [64.45]	85.61 [114.80]	28.00	545.00	10 [145]	100 [1450]
CLP-230	138.58 [36.61]	300.90 [79.49]	105.59 [141.60]	35.00	673.00	10 [145]	100 [1450]
CLP-290	173.90 [45.94]	377.59 [99.75]	132.51 [177.70]	43.00	844.00	10 [145]	100 [1450]
CLP-320	191.58 [50.61]	415.94 [109.88]	139.37 [186.90]	48.00	888.00	10 [145]	100 [1450]
CLP-350	207.29 [54.76]	449.82 [118.83]	147.13 [197.30]	53.00	937.00	10 [145]	100 [1450]
CLP-400	246.39 [65.09]	527.72 [139.41]	162.56 [218.00]	64.00	1035.00	10 [145]	100 [1450]
CLP-440	264.75 [69.94]	567.09 [149.81]	168.53 [226.00]	69.00	1074.00	10 [145]	100 [1450]
CLP-500	299.27 [79.06]	656.39 [173.40]	184.49 [247.40]	76.00	1175	10 [145]	100 [1450]

- High reliability
- Low energy costs
- Easy installation
- Minimum service required

