

CLP 675 pumps CLP-025 - CLP-058

Low flow - B frame (not available for subsea applications)

| Type | Flow l/min. [gpm] | | Pump power | Pump torque | | Discharge pressure | MAWP |
|---------|----------------------|---------------|---------------|-------------|---------|-----------------------|-------------|
| | Min. | Max. | kW [hp] | Min. Nm | Max. Nm | Min. barg [psig] | barg [psig] |
| CLP-025 | 6.13 [1.62] | 23.61 [6.95] | 11.78 [15.80] | 1.80 | 37.00 | 10 [145] | 230 [3336] |
| CLP-035 | 7.91 [2.09] | 33.92 [8.96] | 15.21 [20.40] | 2.30 | 48.00 | 10 [145] | 205 [2973] |
| CLP-042 | 9.73 [2.57] | 41.64 [11.00] | 18.64 [25.00] | 2.80 | 59.00 | 10 [145] | 186 [2698] |
| CLP-050 | 11.55 [3.05] | 49.44 [13.06] | 21.48 [25.80] | 3.40 | 68.50 | 10 [145] | 171 [2480] |
| CLP-058 | 13.55 [3.58] | 57.99 [15.32] | 22.97 [30.80] | 3.90 | 73.00 | 10 [145] | 157 [2277] |

- High reliability
- Low energy costs
- Easy installation
- Minimum service required

