



Subsea Tooling Services Subsea Utility Basket



- Fully DNV 2.7/3 Certified (R30)
- Bail Arm lift point with the option of 4 point corner lift
- ROV Grab Handles
- Drop Down Side Door c/w ROV friendly latches
- 5000 Kg Payload
- Fully Stackable
- Can be used in conjunction with the STS *Predator* Range of Dredgers
- Option of ROV friendly lids
- Deck tie down points

Operational Specification

External Dimensions L x W x H mm	2438mm x 2438mm x 1051 (Height with bail arm extended 2013mm)
Internal Dimensions L x W x H mm	238mm x 238mm x 1051mm
TARE Load	1400 Kg
Payload	5000 Kg
Max Gross Weight	6400 Kg
Depth Rating	5000 MSW
Certification Class	DNV 2.7/3 R30
Lifting Height	4300mm to top of slings with bail arm fully extended
Sling Angle	21 degrees

The STS Subsea Utility Basket has been designed to accommodate the needs of an ROV Support Vessel.

Built to DNV 2.7/3 and coated with Marine grade paint and fitted with external ROV grab handles the STS Subsea Utility Basket is the perfect addition to any subsea construction project.

With a high payload the STS Subsea Utility Basket is the ideal solution for deploying / recovering heavy bulky loads.

Fully stackable & with drop down side door with ROV friendly latches.

