



# Subsea Tooling Services ROV Tooling Basket



- Constructed in accordance with DNV 2.7/3
- H Beam Construction with no box section
- ROV Grab Handles
- Single lift point
- 5000 Kg Payload
- Galvanised Floor & Side Grating
- Can be used in conjunction with the STS *Predator* Range of Dredgers

## Operational Specification

External Dimensions L x W x H mm	2000mm x 2000mm x 2143mm
Internal Dimensions L x W x H mm	1594mm x 1594mm x 797mm
TARE Load	1700 Kg
Payload	5000 Kg
Max Gross Weight	6700 Kg
Depth Rating	5000 MSW
Certification Class	Built in accordance with DNV 2.7-3
Lifting Height	2143mm
Length of sling Pennant	1000mm

The STS ROV Tooling Basket has been designed to accommodate the needs of an ROV / Dive Support Vessel.

Built to DNV 2.7/3 and coated with Marine grade paint and fitted with external ROV grab handles the STS ROV Tooling Basket is the perfect addition to any subsea construction project.

With a high payload the STS ROV Tooling Basket is the ideal solution for deploying / recovering heavy bulky loads.

The STS ROV Tooling Basket is relatively shallow making it easier for the ROV to reach tools. ROV friendly lids come as standard to avoid any tool loss whilst deploying / recovering the basket.

