

THE AVANTIS FLEXI-FIT WINDOW LOCK

Multi-point window locking for high corrosion environments

Manufactured entirely from either stainless or mild steel together with injection-moulded glass filled nylon, to ensure exceptional corrosion resistance in corrosive environments.

Profile specific nylon sliders ensure optimal fit and performance, reducing manufacturing times and extending service life.





FEATURES

- ✓ 20mm and 22mm back sets
- Easy-fit extensions enable simple sizing and offsetting
- ✓ Roller or Mushroom cam locking points
- Mild or stainless steel faceplate
- 10 Year Mechanical guarantee
- Corrosion resistance to EN1670: Grade 5

 (480 hours NSS)*

*Performance on stainless steel faceplate



TECHNICAL SPECIFICATIONS

- √ 15mm wide faceplate
- ✓ 20mm and 22mm backsets
- ✓ 9mm cam height
- 304 grade stainless steel or mild steel faceplate

- 30% glass filled injection-moulded nylon components
- Corrosion resistance to EN1670: Grade 5 (480 hours NSS)*
- ✓ Service life of over 50,000 cycles

*Performance on stainless steel faceplate

22mm BACKSET	20mm BACKSET	SIZE (mm)	CAMS	BOX QUANTITY
WLFF1-250-3S	WLFF2-250-3S	250	2	20
WLFF1-400-3S	WLFF2-400-3S	400	2	20
WLFF1-600-3S	WLFF2-600-3S	600	2	20
WLFF1-800-3S	WLFF2-800-3S	800	2	20
WLFF1-1000-3S	WLFF2-1000-3S	1000	3	20
WLFF1-1200-3S	WLFF2-1200-3S	1200	3	20

EXTENSIONS	PART NUMBER	SIZE (mm)	CAMS	BOX QUANTITY	
Тор	WLFF1-EXT-317-3S	317	1	20	
Bottom	WLFF1-EXT-BTM-3S	317	1	20	



