



Color Bottle System

Liquid Pigments for Adding Color to Select Omega Products



Packaging

4fl oz, 8fl oz, or 16fl oz
(118mL, 236mL, or 473mL)
bottles

Storage

1. Store bottles in a cool, dry location.
2. Store at a temperature between 40°F (4°C) and 90°F (32°C).
3. Store away from direct contact with the ground and/or concrete.
4. Store out of direct sunlight.
5. Protect bottles from weather and other damage.

Shelf Life

1 year

Color

Available in a wide variety of colors. See a current Omega Acrylic Color Chart for stock colors available. Custom colors are available upon request.

Product Description

The **Color Bottle System** is a factory blended, premixed liquid coloring system providing an accurate method for adding pigments to the AkroFlex Finishes, OmegaFlex Finishes, Omega Coatings and other approved Omega products that require liquid integral color.

Features

Benefits

<i>Integral Color</i>	Lasting, uniform color that resists fading or discoloration; UV resistant
<i>Factory Blended</i>	Consistent, repeatable color tinting
<i>Minimal Waste</i>	Eliminates over ordering of premixed colored products
<i>Flexible</i>	Can be used with a variety of products

Basic Uses

The Color Bottle System adds color to AkroFlex Finishes, OmegaFlex Finishes, AkroCoat, RynoTex, AkroFlex Base Primer, RapidPrime, StyroGlue and other approved products.

Area of Use

The Color Bottle System may be used to color the following products:

1. For AkroFlex Finishes, OmegaFlex Finishes, and StyroGlue TF use one bottle per pail. *
2. For AkroFlex Base Primer and RapidPrime use two bottles per pail. *

* Some colors may require two bottles per finish pail and four bottles per primer pail.

Application Instructions



Mixing

1. Shake Color Bottles thoroughly immediately prior to use.
2. Pour contents of bottle into desired pail.
3. Fill bottle with approximately 2 fl oz of potable water.
4. Recap and shake thoroughly.
5. Pour the contents of the bottle into the pail.
6. Repeat steps 1 through 5 for materials requiring two bottles.
7. Drill pail for approximately 3 to 5 minutes.

NOTE: See the appropriate Product Data Sheet for material application instructions.

Limitations

DO NOT mix product when the ambient and surface temperature is below 40°F (4°C).

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International.

DO NOT deviate in the mixing or application procedures contained in this, or any other Product Data Sheets, without written approval from Omega Products International.

DO NOT use a paddle mixer that exceeds 500 RPM.

DO NOT add any more water than prescribed.

DO NOT use expired Color Bottles.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Cleaning

Cleaning may be accomplished with water immediately after use.

Safety

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

COLOR BOTTLE SYSTEM

www.omega-products.com

Disclaimer

Omega Products International [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT(S) SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufac-

turer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product

for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

Claims

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect.

For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

Technical Assistance

Technical assistance and information is available by calling Omega Products International at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

Warranty

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.