

Fre-Thane® Polyurethane Coils



Fre-Thane® polyurethane coils possess outstanding memory, a soft feel and superior flexibility. These coils are extraordinarily tough and resistant to abrasion, overstretching, kinking and repeated flexing.

Variations are easy. If you don't see the color or length that you want, just ask us. We can configure Fre-Thane® Coils to perfectly match your requirements.

Specifications

Temperature Range
-40°F to +125°F

Vacuum Rating
To 28" Hg.

Diameter Tolerances
±.005"

Working Pressure
3:1 Safety Factor

UV Stabilized
95A & 85A

Resin Compliance
See Page 8 for
Fre-Thane Compliances

Suggested Fittings
Barb, Push-In (95A)

Standard Tail Lengths
8" and 16"

Fre-Thane® Single Tube Polyurethane Coils

Part Number & Color Code	OD	ID	DUR	Standard Colors	Working Pressure		Material Length	Working Length	Retracted Length	Coil ID
					75°F/25°C	150°F/65°C				
1W-013-___	1/8"	.066"	85A	01 02 04 05 06 07 08 09 10 11 12 14 25 26 27 28 29 32 45 46	115 PSI	45 PSI	10'	8'	8"	3/8"
1W-025-___	1/4"	1/8"	85A	01 02 04 05 06 07 08 09 10 11 12 25 26 27 28 29 32 46	125 PSI	50 PSI	10'	8'	5"	3/4"
1W-132-___	1/4"	.159"	90A	01 07 08 10 14 25 27	115 PSI	45 PSI	10'	8'	5"	3/4"
1W-005-___	3/8"	.245"	90A	01 05 07 10 11 25 27	105 PSI	40 PSI	10'	8'	7.5"	1-1/4"
1Z-005-___					25'	20'	22"			
1W-151-___	1/4"	.16"	95A	01 04 05 06 07 08 09 10 11 12 25 26 27 28 46	150 PSI	60 PSI	10'	8'	7"	1"
1X-151-___	1/4"	.16"	95A				15'	12.5'	9.5"	
1Y-151-___	1/4"	.16"	95A				20'	17'	12.5"	
1Z-151-___	1/4"	.16"	95A				25'	20'	15.5"	
1W-152-___	3/8"	.245"	95A	01 04 05 06 07 08 10 11 25 26 27 28 37 46	130 PSI	60 PSI	10'	8'	6"	1-3/4"
1X-152-___	3/8"	.245"	95A				15'	12.5'	9.5"	
1Y-152-___	3/8"	.245"	95A				20'	17'	13"	
1Z-152-___	3/8"	.245"	95A				25'	20'	16"	

Variations Available:

Colors • Cutting • Bonding • Printing • Packaging • Sizes

Metric Fre-Thane® Single Tube Polyurethane Coils

Part Number & Color Code	OD	ID	DUR	Standard Colors	Working Pressure		Material Length	Working Length	Retracted Length	Coil ID	Tail Length
					75°F/25°C	150°F/65°C					
1W-156-___	4mm	2.4mm	95A	01 02 04 05 06 07 08 09 10 11 12 25 26 27 28 37	165 PSI	85 PSI	3.05 M	2.6 M	133.4mm	19.1mm 16.99/33.9mm	
1X-156-___	4mm	2.4mm	95A				4.57 M	3.8 M	216mm		
1Y-156-___	4mm	2.4mm	95A				6.1 M	5.2 M	292mm		
1Z-156-___	4mm	2.4mm	95A				7.62 M	6.4 M	381mm		
1W-158-___	6mm	4mm	95A	01 04 05 06 07 08 09 10 11 25 26 27 28 37	135 PSI	65 PSI	3.05 M	2.6 M	139.7mm	25.4mm 16.9/33.9mm	
1X-158-___	6mm	4mm	95A				4.57 M	3.8 M	241.3mm		
1Y-158-___	6mm	4mm	95A				6.1 M	5.2 M	330mm		
1Z-158-___	6mm	4mm	95A				7.62 M	6.4 M	419mm		
1W-159-___	8mm	5mm	95A				01 05 06 07 08 10 11 25 27 37 46	160 PSI	75 PSI		3.05 M
1X-159-___	8mm	5mm	95A	4.57 M	3.8 M	254mm					
1Y-159-___	8mm	5mm	95A	6.1 M	5.2 M	343mm					
1Z-159-___	8mm	5mm	95A	7.62 M	6.4 M	444.5mm					
1W-160-___	10mm	6.5mm	95A	01 05 06 07 08 10 27	135 PSI	70 PSI	3.05 M	2.6 M	139.7mm	44.5mm 16.9/33.9mm	
1X-160-___	10mm	6.5mm	95A				4.57 M	3.8 M	228.6mm		
1Y-160-___	10mm	6.5mm	95A				6.1 M	5.2 M	317.5mm		
1Z-160-___	10mm	6.5mm	95A				7.62 M	6.4 M	406.4mm		

Variations Available:

Colors • Cutting • Bonding • Printing • Packaging • Sizes