


## Function Fittings - Ball Valves

**7913**

**Mini Ball Valve** - 3/2 With Vent & Push-In Connection, Polymer


ØD	P/N
4	7913 04 00
6	7913 06 00
8	7913 08 00
10	7913 10 00
12	7913 12 00

**7910**

**Mini Ball Valve** - 2/2 With Push-In Connection, Polymer


ØD	P/N
4	7910 04 00
6	7910 06 00
8	7910 08 00
10	7910 10 00
12	7910 12 00

**06065**

**Mini Ball Valve** - Female ISO228 To Female ISO228, Nickel-Plated Brass


ØD	P/N
1/8	06065 00 001
1/4	06065 00 002
3/8	06065 00 003
1/2	06065 00 004
3/4	06065 00 005

**06066**

**Mini Ball Valve** - Male ISO228 To Female ISO228, Nickel-Plated Brass


ØD	P/N
1/8	06066 00 001
1/4	06066 00 002
3/8	06066 00 003
1/2	06066 00 004
3/4	06066 00 005

**4905**

**"Economy" Female To Female** With Standard Handle, BSP Parallel, Nickel-Plated Brass


C	DN	PN	P/N
G1/4	10	25	4905 00 13
G3/8	10	25	4905 00 17
G1/2	14	25	4905 00 21
G3/4	20	25	4905 00 27
GI	25	25	4905 00 34
GI 1/4	32	16	4905 00 42
GI 1/2	40	16	4905 00 49
G2	50	16	4905 00 48

**L100**

**2-Way Full Bore**, Female To Female, Suitable for Low Pressures, Nickel-Plated Brass


ØD	P/N
3/8	DN 10
1/2	DN 15
3/4	DN 20
1	DN 25
1 1/4	DN 32
1 1/2	DN 40
2	DN 50

**06300**

**Female RP ISO 7 To Female RP ISO 7 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06300 00 001
1/4	1/4	06300 00 002
3/8	3/8	06300 00 003
1/2	1/2	06300 00 004
3/4	3/4	06300 00 055

**06310**

**Taper Male R ISO 7 To Female RP ISO 7 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06310 00 001
1/4	1/8	06310 00 002
1/4	1/4	06310 00 003
3/8	3/8	06310 00 004
1/2	1/2	06310 00 005
3/4	3/4	06310 00 066

**06410**

**Parallel Male GA ISO 228 To Female G ISO 228 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06410 00 001
1/4	1/8	06410 00 002
1/4	1/4	06410 00 003
3/8	3/8	06410 00 004
1/2	1/2	06410 00 005
3/4	3/4	06410 00 066

**06320**

**Parallel Male GA ISO 228 To Female RP ISO 7 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06320 00 001
1/4	1/8	06320 00 002
1/4	1/4	06320 00 003
3/8	3/8	06320 00 004
1/2	1/2	06320 00 005
3/4	3/4	06320 00 066

**06330**

**Taper Male R ISO 7 To Parallel Male GA ISO 228 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06320 00 001
1/4	1/8	06320 00 002
1/4	1/4	06320 00 003
3/8	3/8	06320 00 004
1/2	1/2	06320 00 005
3/4	3/4	06320 00 066

**06400**

**Female G ISO 228 To Female G ISO 228 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06400 00 001
1/4	1/4	06400 00 002
3/8	3/8	06400 00 003
1/2	1/2	06400 00 004
3/4	3/4	06400 00 055

**06710**

**3-Way Valve 'T' Female G ISO 228**, Nickel-Plated Brass


ØD	ØD	ØD	P/N
1/8	1/8	1/8	06710 00 001
1/4	1/4	1/4	06710 00 002
3/8	3/8	3/8	06710 00 003

**06560**

**Push-In Connection**, Nickel-Plated Brass


ØD	C	P/N
4	4	06560 00 001
6	6	06560 00 002
8	8	06560 00 003
10	10	06560 00 075
12	12	06560 00 076

**06600**

**Exhaust Hole Female G ISO 228 To Female G ISO 228 Valve**, Nickel-Plated Brass


ØD	C	P/N
1/8	1/8	06600 00 001
1/4	1/4	06600 00 002
3/8	3/8	06600 00 003

**06700**

**3-Way Valve 'L' Female G ISO 228**, Nickel-Plated Brass



ØD	ØD	ØD	P/N
1/8	1/8	1/8	06700 00 001
1/4	1/4	1/4	06700 00 002
3/8	3/8	3/8	06700 00 003

**06720**

**'L' Female G ISO 228 Valve**, Nickel-Plated Brass


ØD	ØD	P/N
1/8	1/8	06720 00 001
1/4	1/4	06720 00 002
3/8	3/8	06720 00 003

**06755L**

**Lockable With Exhaust Vent**, Nickel-Plated Brass


ØD	P/N
3/8	06755 L0 001
1/2	06755 L0 002
3/4	06755 L0 003
1	06755 L0 004
1 1/4	06755 L0 005
1 1/2	06755 L0 006
2	06755 L0 007

**06920**

**Plastic - Coloured Plate For Handles**


Type	P/N
A	06920 A0 30 00 RO
B	06920 B0 30 00 RO
A	06920 A0 30 00 GI
B	06920 B0 30 00 GI
A	06920 A0 30 00 BL
B	06920 B0 30 00 BL
A	06920 A0 30 00 VE
B	06920 B0 30 00 VE
A	06920 A0 30 00 VE
B	06920 B0 30 00 VE

**06910**

**Plastic - Long Handle**


Type	Size	P/N
A	1/8, 1/4, 3/8	06910 A0 30 00 00
B	1/2, 3/4	06910 B0 30 00 00

**0439**

**Lockable**, Female To Female With Vent, Nickel-Plated Brass


C	DN	P/N
G1/4	7	0439 07 13
G3/8	10	0439 10 17
G1/2	13	0439 13 21

**06915**

**Spindle Extension With Long Handle & Screw**


Type	Size	P/N
A	1/8, 1/4, 3/8	06915 00 001
B	1/2, 3/4	06915 00 002

## L424



Stainless Steel - **2-Way Full-Bore**  
3 Piece Casted Threaded-Ends  
Or Butt Weld, PTFE Seals



ØD	P/N
1/4	DN 08
3/8	DN 10
1/2	DN 15
3/4	DN 20
1	DN 25
1 1/4	DN 32
1 1/2	DN 40
2	DN 50
2 1/2	DN 65
3	DN 80
4	DN 100

## 4810



Stainless Steel - **"Economy"**  
**Version**, Female To Female, BSP  
Parallel



C	DN	P/N
G1/4	8	4810 08 13
G3/8	10	4810 10 17
G1/2	15	4810 15 21
G3/4	20	4810 20 27
G1	25	4810 25 34

## LHA



**High Ciclicity Ball Valves**

Range of 4: Carbon Steel, Carbon Steel (Manual Operated),  
Stainless Steel, & Stainless Steel PTFE-TFM1600 seats

Fluid range: Different fluids,  
liquid and gaseous, compatible with  
constituent materials.

Antistatic, & FireSafe Design

\* Please contact us for sizes & part numbers



## Function Fittings - Silencers

### 0670



**Threaded Silencer** - Nickel-Plated  
Brass/Sintered Bronze, Threaded  
BSP Parallel



ØD	P/N
G1/8	0670 00 10
G1/4	0670 00 13
G3/8	0670 00 17
G1/2	0670 00 21
G3/4	0670 00 27
G1	0670 00 34

### 0671



**Push-In Silencer** - Nickel-Plated  
Brass/Sintered Bronze



ØD	P/N
4	0671 04 00
6	0671 06 00
8	0671 08 00
10	0671 10 00
12	0671 12 00

### 0672



**Flow Control Silencer** - Nickel-  
Plated Brass/Sintered Bronze,  
Male BSP Parallel



ØD	P/N
G1/8	0672 00 10
G1/4	0672 00 13
G3/8	0672 00 17
G1/2	0672 00 21

### 07050



**Flow Control Silencer** - Brass  
Sintered Bronze



ØD	P/N
1/8	07050 00 001
1/4	07050 00 002
3/8	07050 00 003
1/2	07050 00 004

### 0673



**Compact Silencer** - Brass/  
Sintered Bronze, Threaded BSP  
Parallel, Metric & UNF



ØD	P/N
G1/8	0673 00 10
G1/4	0673 00 13
G3/8	0673 00 17
M5x0,8	0673 00 19
10-32	0673 00 20
G1/2	0673 00 21

### 07070



**Threaded Silencer** - Acetel Resin  
& Plastic Soundproofing Material



ØD	P/N
1/8	07070 00 001
1/4	07070 00 002
3/8	07070 00 003
1/2	07070 00 004
3/4	07070 00 005
1	07070 00 006

### MSR



**Plastic Silencer** - Operating  
Pressure Range: 0 to 0.9MPa  
Ambient Temp.: 0 to +60C



ØD	P/N
1/8	MSR01-S
1/8	MSR01-B
1/4	MSR02-S
1/4	MSR02-B

### 0674



**Threaded Silencer** - Male BSP  
Parallel & Metric



ØD	P/N
G1/8	0674 00 10
G1/4	0674 00 13
G3/8	0674 00 17
M5x0,8	0674 00 19
G1/2	0674 00 21
G3/4	0674 00 27
G1	0674 00 34

### 0676



**Flow Control Silencer** - Male BSP  
Parallel



ØD	P/N
G1/8	0676 00 10
G1/4	0676 00 13
G3/8	0676 00 17
M5x0,8	0676 00 19
G1/2	0676 00 21

### B##



**'Bantam' Muffler** - Zinc-Plated  
Steel & Brass Acoustic Element  
\* Male Option Available In Stainless



ØD	P/N	ØD	P/N
1/8	*B18	1	*B88
1/4	*B28	1 1/4	B108
3/8	*B38	1 1/2	B128
1/2	*B48	2	B168
3/4	*B68		

### B##



**'Bantam' Muffler** - Zinc-Plated  
Steel & Brass Acoustic Element,  
Female Options: 1/8" to 1/2"



ØD	P/N
1/8	B18
1/4	B28
3/8	B38
1/2	B48