



Specification Table

(NKM DPK series Dispersion Mixer)

Model	Total Volume	Working Volume	Motor Power	Tilting Motor	Feeding Position	Speed	Air Pressure	Tilting Angle
	Liter	Liter	kW	kW		rpm	Mpa	
DPK-3	3	1	3	0.18	Front	32/27	0.6-0.8	110°
DPK-12	12	5	11	0.75	Front	32/27	0.6-0.8	110°
DPK-20	20	8	22	1.5	Front	32/27	0.6-0.8	110°
DPK-35	35	15	30	2.2	Front	32/27	0.6-0.8	110°
DPK-55F	55	25	37	4	Front	32/27	0.6-0.8	110°
DPK-55R	55	25	37	4	Rear	32/27	0.6-0.8	110°
DPK-75F	75	35	55	4	Front	30/24.5	0.8-1.0	145°
DPK-75R	75	35	55	4	Rear	30/24.5	0.8-1.0	110°
DPK-110F	110	50	90	5.5	Front	30/24.5	0.8-1.0	145°
DPK-110R	110	50	90	5.5	Rear	30/24.5	0.8-1.0	110°
DPK-150R	150	70	110	7.5	Rear	30/24.5	0.8-1.0	145°
DPK-300R	300	125	220	11	Rear	30/24.5	0.8-1.0	145°

- Note: 1. Special trough sizes are available upon request.
2. The motor power can vary upon different material characters.
3. Arm speed can be specially designed.
4. NKM reserves the right to modify the specifications without notice in advance.