



Specification Table

(NKM VM series V Blender)

| Model | Total Volume | Working Volume | Motor Power | Shaft Speed | Total Height | Weight |
|---------|--------------|----------------|-------------|-------------|--------------|--------|
| | Liter | Liter | kW | RPM | mm | Kg |
| VM-2 | 2 | 1 | 0.37 | 15 | 500 | 50 |
| VM-5 | 5 | 3 | 0.37 | 15 | 800 | 60 |
| VM-20 | 20 | 10 | 0.55 | 15 | 1,100 | 75 |
| VM-60 | 60 | 35 | 0.75 | 15 | 1,700 | 150 |
| VM-120 | 120 | 70 | 1.1 | 15 | 1,950 | 350 |
| VM-300 | 300 | 180 | 1.5 | 15 | 2,200 | 450 |
| VM-500 | 500 | 300 | 2.2 | 15 | 2,500 | 500 |
| VM-1000 | 1,000 | 600 | 3 | 12 | 2,700 | 820 |
| VM-1500 | 1,500 | 900 | 4 | 10 | 3,200 | 900 |
| VM-2000 | 2,000 | 1,200 | 5.5 | 10 | 3,550 | 1,000 |
| VM-4000 | 4,000 | 2,400 | 11 | 10 | 3,900 | 1,200 |

- Note: 1. Special sizes are available upon request.
2. The motor power can vary upon different material characters.
3. Shaft speed can be specially designed or variable speed controlled.
4. NKM reserves the right to modify the specifications without notice in advance.