


Silverstar®


Einsatzbereiche: Stahl allgemein,
Guss- und Schweißnähte.

Kühl schleifend, hohe Standzeit, doppelt
kunstharzgebunden.
Stützteller erforderlich.


Application: Steel in general,
casting and welding seams.

Cool grinding, long lifetime, double bonded
with synthetic resin.
Use always with backing pads.



Abmessungen Dimensions [mm]	Abmessungen Dimensions [Zoll/Inch]	Korngröße Grit size	EAN/Art.Nr. 4103510 Form 22	
Korund – Aluminiumoxide				
115 x 22/3	4 1/2 x 7/8	ASE 24	00541 4	25
115 x 22/3	4 1/2 x 7/8	ASE 40	00544 5	50
115 x 22/3	4 1/2 x 7/8	ASE 60	00546 9	50
115 x 22/3	4 1/2 x 7/8	ASE 80	00547 6	50
115 x 22/3	4 1/2 x 7/8	ASE 120	00549 0	50
125 x 22/3	5 x 7/8	ASE 24	00553 7	25
125 x 22/3	5 x 7/8	ASE 40	00556 8	50
125 x 22/3	5 x 7/8	ASE 60	00558 2	50
125 x 22/3	5 x 7/8	ASE 80	00559 9	50
125 x 22/3	5 x 7/8	ASE 120	00561 2	50
180 x 22/3	7 x 7/8	ASE 24	00570 4	25
180 x 22/3	7 x 7/8	ASE 40	00573 5	50
180 x 22/3	7 x 7/8	ASE 60	00575 9	50

Stützteller – Backing pads

Abmessungen Dimensions [mm]	Abmessungen Dimensions [Zoll/Inch]	EAN/Art.Nr. 4103510	
115 x M 14	4 1/2 x M14	00460 8	1
125 x M 14	5 x M14	00461 5	1
180 x M 14	7 x M14	00463 9	1