































## Piestne tesnenie

Pohyb	Profil	Typ	Materiál	Rýchlosť	Teplota	Tlak [bar]	Poznámky:
		PS 01	PU NBR FPM	0,5 m/s	(-30; 105)°C (-25; 100)°C (-20; 210)°C	400 160 160	štand. tesnenie
		PS 01 A	PU NBR FPM	0,5 m/s	(-30; 105)°C (-25; 100)°C (-20; 210)°C	160 160 160	
		PS 01 B	PU NBR FPM	0,5 m/s	(-30; 105)°C (-25; 100)°C (-20; 210)°C	400 160 160	
		PS 02	PU/POM NBR/POM FPM/PTFE	0,5 m/s	(-30; 105)°C (-25; 100)°C (-20; 210)°C	700 250 250	
		PS 02 A	PU/POM NBR/POM FPM/PTFE	0,5 m/s	(-30; 105)°C (-25; 100)°C (-20; 210)°C	700 250 250	
		PS 03	PU/NBR	0,5 m/s	(-25; 100)°C	400	
		PS 04	PU/NBR/POM	0,5 m/s	(-25; 100)°C	700	
		PS 05	PU NBR	1 m/s	(-30; 105)°C (-25; 100)°C	25	
		PS 06	PU-D57/NBR PTFE/NBR	1 m/s 15 m/s	(-25; 100)°C	250 400	štand. tesnenie, väčšia pohyblivosť, bez stick-slip efektu
		PS 06 A	PU-D57/NBR PTFE/NBR	1 m/s 15 m/s	(-25; 100)°C	250 400	štand. tesnenie
		PS 06 B	PU-D57/NBR PTFE/NBR	1 m/s 10 m/s	(-25; 100)°C	250 400	štand. tesnenie
		PS 06 C	PTFE/NBR	2 m/s	(-25; 100)°C	400	
		PS 06 D	PTFE/NBR	3 m/s	(-25; 100)°C	400	
		PS 06 E	PU-D57/NBR PTFE/NBR	1 m/s 10 m/s	(-25; 100)°C	250 400	
		PS 06 F	PU-D57/NBR	0,5 m/s	(-25; 100)°C	250	štand. tesnenie

## Piestne tesnenie

Pohyb	Profil	Typ	Materiál	Rýchlosť	Teplota	Tlak [bar]	Poznámky:
		PS 07	PU-D57/NBR PTFE/NBR	1 m/s 10 m/s	(-25; 100)°C	250 400	
		PS 08	PU/NBR/POM	0,5 m/s	(-25; 100)°C	400	bez slip-stick efektu, zlepšená odolnosť proti opotrebeniu
		PS 08 A	PTFE/NBR/PO M	1 m/s	(-25; 100)°C	400	
		PS 09	NBR	0,5 m/s	(-25; 100)°C	160	
		PS 09 A	NBR	0,5 m/s	(-25; 100)°C	160	
		PS 10	PU/POM NBR/POM	0,5 m/s	(-25; 100)°C	400 250	
		PS 10 A	PU/POM NBR/POM	0,5 m/s	(-25; 100)°C	400 250	štand. tesnenie
		PS 10 B	PU/POM NBR/POM	0,5 m/s	(-25; 100)°C	400 250	
		PS 11	PTFE-FV/ pružina	15 m/s	(-200; 260)°C	160	
		PS 12	NBR/POM	0,5 m/s	(-25; 100)°C	700	
		PS 13	PU/NBR/POM	0,5 m/s	(-25; 100)°C	400	
		PS 14	PU	0,4 m/s	(-30; 105)°C	400	