

CTL3510

GPS Jammer Detector



Product Overview

The Chronos CTL3510 GPS Jammer Detector is a low cost, handheld, battery operated device designed to detect the presence of GPS jamming or too much power or interference in the GPS (L1) band.

- Ideal for detecting commercially available GPS jammers hidden in vehicles
- Time stamped event logging feature enables covert deployment in vehicles where the driver is suspected of using GPS Jammers



CTL3510 in cradle attached to windscreen

Applications - GPS Jammer Detection

Detection and location of GPS jammers in:

- Any vehicle or human carrier
- Multi-storey car parks
- Taxi ranks at railway stations, airports etc.
- Truck holding areas
- Van depot gates
- Ports, freight & container terminals

Applications - GPS Antenna Installation

- Routine checking of new and existing GPS antenna installations
- Detection of spurious emissions caused by cable/connector corrosion impedance mismatch

Key Features

- Simple to use
- Detects GPS jamming at 1575.42 MHz (GPS - L1)
- High sensitivity
- Time stamped event logging
- Visual LED display of jammer strength
- Vibrate alert
- Hand held - small size, light weight
- Rechargeable battery via mini USB
- Low battery indicator

Users Include

- Law Enforcement Agencies
- Communications Licensing Regulators
- Security Operatives
- Fleet Operators
- Critical Infrastructure Operators
- GPS Installation Engineers

DATASHEET

CTL3510

GPS Jammer Detector



Specifications

Detection Capability

The CTL3510 detects power in the GPS L1 band over a 20MHz bandwidth at 1575.42 MHz and displays jammer power using 8 LEDs.

LED Signal Strength Indications

- 8 LED jammer power signal strength indicators centred at 1575.42MHz (GPS L1)
- Each LED indicates strength in approximately 5dB steps
- Yellow LEDs indicate lower power and red LEDs indicate higher power

Switches

- Power on/off
- Battery charge indicator LED
- Peak hold to indicate maximum power detected

Event Logging

- Time stamping of events with USB download to PC
- PC App supplied to interface to CTL3510 to run on Windows 32/64 bit platform

Temperature

Range for normal operation: -20°C to +60°C

Physical

Case: 65 x 105 x 19mm
Weight: 82 grams (including battery)
Battery: Rechargeable lithium polymer battery
Battery Life: 24 hours

Supplied Accessories

USB Power Supply and USB cable for charging battery and connection to PC

Optional Accessories

CTL3510 universal mount with twist body suction cup base designed to have a strong hold on glass and non-porous plastic surfaces. The mount rubber ball and socket system has adjustment points at both ends of the double socket arm allowing for almost infinite adjustment and perfect viewing angles.



Typical Jammers detectable with the CTL3510



DATASHEET

© 2016 Chronos Technology. Specifications subject to change without notice.

GPS World from Chronos Technology

Chronos Technology Limited Stowfield House Upper Stowfield Lydbrook Gloucestershire GL17 9PD UK
Tel: +44 (0)1594 862200 Email: sales@chronos.co.uk www.chronos.co.uk www.gps-world.biz

