



AMP1064 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class AB linear GaN design
- Instantaneous wide bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	20 - 6000 MHz	
Power Output	20 Watt Min / 25 Watt Typ	
Power Gain	44 dB Min	
Power Gain Flatness	4 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>26 dBc Typ	33dBm/Tone, $\Delta = 1$ MHz
Harmonics	>15 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc Min	
Operating Voltage	50 VDC Nom	
Current Consumption	3 Amp Max	At rated Pout
Max Input Power	+3 dBm	Without damage
Load VSWR Protection	5 : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	140 X 90 X 27 mm	Excluding Connectors
Weight	600 gr.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	N/A
2	VVA	Reserved
3	CURRENT SENSOR	$I_D @ 50mV/100mA$ Typ
4	TEMP SENSOR	$V_T @ 10mV/°C + 500mV$ Typ
5	SHUTDOWN	TTL
6, 7	VDD	50VDC
8, 9	GND	Ground

AMP1064 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

