

AMSOIL MSDS

Ingredient name	%
Solvent naphtha, light aromatic	60 - 100
Trimethylbenzene	30 - 60
1,2,4-Trimethylbenzene	10 - 30
Solvent naphtha, heavy aromatic	10 - 30
1,2,3-Trimethylbenzene	10 - 30
Mesitylene	10 - 30
Cumene	1 - 5
2-Butoxyethanol	1 - 5
Xylene	1 - 5
Naphthalene	1 - 5

STANADYNE MSDS

64742-47-8	Distillates, petroleum, hydrotreated light	30-50
27247-96-7	2-Ethylhexyl nitrate	20-30
64742-94-5	Naphtha (petroleum), heavy aromatic	10-30
111-76-2	Ethylene glycol monobutyl ether	3-7
25551-13-7	Trimethylbenzene (mixed)	1-5
91-20-3	Naphthalene	1-3
95-63-6	1,2,4-Trimethylbenzene	0.1-0.6

SEAFOAM MSDS

Chemical name	CAS #	Concentration
Hydrocarbon blend*	Blend	< 95%
Isopropanol	67-63-0	< 25%

*Note: The exact composition of the above listed chemicals are being withheld as a trade secret.

Isopropanol: Also called isopropyl alcohol. Often used as a solvent to dissolve oils and to clean brake fluid.

E-ZOIL MSDS

Name	CAS Number	%
Ethylene glycol butyl ether	111-76-2	60 - 80
Triethylamine	102-71-6	1 - 5
Fatty Acid	Trade Secret	1 - 5
Benzene, trimethyl-	25551-13-7	1 - 5
1,3,5-Trimethylbenzene	108-67-8	1 - 5
Naphthalene	91-20-3	1 - 5

Ethylene glycol butyl ether: (also known as 2-Butoxyethanol) A nonvolatile, inexpensive solvent. Used in paints, coatings, cleaning products and inks. Also used in fracturing fluids, drilling stabilizers and oil spill dispersants.