





















AVANT 630 AVANT 635 AVANT 640

| | | | | | |
|---|--------------|---|----------------|---|----------------|
|  | 2400 lb |  | 2400 lb |  | 2400 lb |
|  | 25 hp diesel |  | 37.5 hp diesel |  | 37.5 hp diesel |
|  | 112 in |  | 112 in |  | 112 in |
|  | 9 MPH |  | 9 MPH |  | 14 MPH |
|  | 3310 lb |  | 3370 lb |  | 3500 lb |
|  | 100 in |  | 100 in |  | 100 in |



600 series



Technical data

| Model | AVANT 630 | AVANT 635 | AVANT 640 |
|--|--------------------------|--------------------------|--------------------------|
| Length | 100.3 in | 100.3 in | 100.3 in |
| Width (with 26x12.00-12 wheels) | 50.8 in | 50.8 in | 50.8 in |
| Height | 80.2 in | 80.2 in | 80.2 in |
| Weight | 3310 lb | 3370 lb | 3500 lb |
| Standard wheels | 26x12.00-12" TR or grass | 26x12.00-12" TR or grass | 26x12.00-12" TR or grass |
| Transmission, drive | hydrostatic | hydrostatic | hydrostatic |
| Drive speed (max.) | 9 MPH | 9 MPH | 14 MPH |
| Auxiliary hydraulics oil flow / pressure | 11.6 gal/min 2900 psi | 17.4 gal/min 2900 psi | 17.4 gal/min 2900 psi |
| Hydraulic oil cooler | Standard | Standard | Standard |
| Turning radius inside/outside* | 35.4 / 86.2 in | 35.4 / 86.2 in | 35.4 / 86.2 in |
| Max. lifting height | 112 in | 112 in | 112 in |
| Max. tipping load** | 2400 lb | 2400 lb | 2400 lb |
| Max. breakout force | 2700 lb | 2700 lb | 2700 lb |
| Engine make and type | Kubota D1105 | Kubota V1505 | Kubota V1505 |
| Engine output (ISO Gross) | 25 hp | 37.5 hp | 37.5 hp |
| Fuel | Diesel | Diesel | Diesel |

* Turning radius with 26x12.00-12 wheels

** Load is measured at 15.8 in from the attachment coupling plate, Including attachment weight of 155 lb.

Height with Cab

| Wheel size | 26x12.00-12 or 320/60-12 | 27x8.50-15 |
|---|--------------------------|------------|
| Cab LX | 79.7 in | 80.2 in |
| Cab DLX | 80.5 in | 81.0 in |
| Cab DLX with Air conditioning on the roof | 85.9 in | 86.4 in |

Width

| Wheel size | Profile | Machine width |
|-----------------|-------------|---------------|
| 27 x 8.50 - 15 | TR | 40.0 in |
| 26 x 12.00 - 12 | TR or grass | 50.8 in |
| 320/60 - 12 | TR | 50.8 in |

Options

Boom floating, Hydraulic attachment coupling plate, Attachment control switch pack, Rear auxiliary hydraulics, Extra front auxiliary hydraulics, Road traffic light kit, Work light kit, Rear side weights 400 lb, Extra weights, trailer coupling, Engine block heater, Tilt adapter, Catalytic converter, Beacon, Snow chains, Weather cover, Full weather cover, Anti slip valve, Cab L, Cab LX, Cab DLX, Air conditioning, Air suspension seat.



Avant Tecno USA Inc.

3020 Malmo Drive, Arlington Heights, IL 60005

847.380.9822 phone, 847.380.9823 fax

e-mail: sales@avanttecnousa.com

AVANT has a policy of continuing improvement, and retains the right to change specifications without notice. © 2014 AVANT Tecno Oy. All rights reserved.

www.avanttecnousa.com