



Gunnebo Johnson Corporation > [Gunnebo Classic Alloy Chains and Fittings](#) > [Coupling Links](#) > [Mechanical Connector \(Link-G\)](#)

Mechanical Connector (Link-G)

- Used as a top fitting to attach chain legs to master link
- Often used as a bottom fitting to attached plate clamp, engineered device, or shackle to chain sling leg
- Wide Body (B dimension) for extra room
- Heavy duty galvanized retaining collar houses square stainless steel locking spring
- Center pin has recess for strong mechanical lock.
- Full traceability
- Proof tested to 2 ½ times working load limit



MODEL	CHAIN SIZE	GRADE	WORKING LOAD LIMIT	DIMENSIONS (Inches)				WEIGHT EACH
				L	B	G	E	
	Inches		* (lbs) at 90°					lbs
G-7-10	9/32	100	4,300	2.2	0.71	0.35	0.87	0.44
G-8-10	5/16	100	5,700	2.2	0.71	0.35	0.87	0.44
G-10-10	3/8	100	8,800	2.7	0.98	0.47	1.0	0.66
G-13-10	1/2	100	15,000	3.5	1.1	0.59	1.3	1.5
G-16-10	5/8	100	22,600	4.1	1.4	0.75	1.6	2.6
G-20-10	3/4	100	35,300	4.9	1.7	1.0	2.8	5.7
G-22-8	7/8	80	34,200	6.0	2.0	0.95	2.3	6.6
G-26-8	1	80	47,700	6.3	2.3	1.1	2.4	10.1
G-32-8	1-1/4	80	72,300	7.9	2.8	1.5	3.1	19.0

* Design Factor 4:1 Proof tested and certified
Unlimited number of assemblies / disassemblies.

