



Gunnebo Johnson Corporation > [Gunnebo Classic Alloy Chains and Fittings](#) > [Shortening and Choking Device](#) > [Eye Grab, Cradle Type \(OG\)](#)

Eye Grab, Cradle Type (OG)

- Eye design allows connection closer to the master link for a "Type A" shortener
- Chain is cradled on cross bar so there is no reduction in working load limit of a shortened leg as long as the sling leg angle does not change
- Deep chain pocket design
- Full traceability
- Proof tested and certified



MODEL	CHAIN SIZE (INCHES)	GRADE	WORKING LOAD LIMIT * (Lbs) at 90°	DIMENSIONS (INCHES)				WEIGHT Lbs
				L	B	E	F	
OG-7/8-8	9/32	80	3,500	2.6	0.39	0.63	0.39	0.66
OG-7/8-8	5/16	80	4,500	2.6	0.39	0.63	0.39	0.66
OG-10-8	3/8	80	7,100	3.3	0.47	0.79	0.47	1.3
OG-13-8	1/2	80	12,000	4.1	0.59	0.99	0.63	2.6
OG-16-8	5/8	80	18,100	5.1	0.75	1.1	0.75	5.3
OG-19/20-8	3/4	80	28,300	6.1	0.89	1.4	0.91	10.1
OG-22-10	7/8	100	42,700	7.4	1.0	1.8	1.3	19
OG-26-10	1	100	59,700	9.0	1.3	2.2	1.5	30.9

*Desin Factor 4:1 Proof tested and certified.

**Not intended for use with BL Coupler

***Grade 80 hooks are the "Classic safety yellow color

****Grade 100 hooks are the "GabiQ signal yellow color

