




Split Overhaul Ball

- Attaches easily to Wireline.




Split Overhaul Ball

Catalog No.	Stock No.	Wireline Size (in.)	Weight Each (lbs.)	Belt Diameter A (in.)
SHB - 15	2003822	1/4-5/16	15	5.06
SHB - 20	2003830	3/8	20	5.38
SHB - 50	2003831	1/2 - 5/8	50	7.12
SHB - 100	2003832	5/8 - 3/4 - 7/8	100	9.19



AS-15 Overhaul Ball

- Utilize genuine Crosby hooks which are forged alloy steel, Quenched and Tempered and contain the patented **QUIC-CHECK®** marking.
- Entire overhaul ball is zinc plated to resist corrosion.
- Designed with angular contact bearings which maximize efficiency, reliability and service life of swivel and extend the life of the Wireline.
- Available with wide jaw opening that utilizes nylon spools and shields.
- Designed for applications where headroom is critical.
- Other upper fittings available upon request.



Angular Contact Bearing Swivel Overhaul Balls

AS-15 Stock No.	Working Load Limit (Tons)*	Wireline Size (in.)	Dimensions (in.)													Weight Each (lbs.)
			A	B	C	D	E	F	G	H	I	J	K	L		
2009806	1.5	.38	4.00	.50	.50	.69	.78	6.28	4.09	1.12	1.22	1.19	1.12	.31	9	
2009807	3.0	.50	5.00	.75	.75	.94	1.19	8.56	4.94	1.34	1.50	1.38	1.44	.38	19	
2003969	5.0	.62	6.88	.88	1.06	1.12	1.56	10.81	6.50	1.69	1.88	1.75	1.81	.56	43	
2009808	8.5	.75	7.00	1.19	1.56	1.34	2.09	13.75	8.69	2.25	2.50	2.56	2.59	.53	60	

* Ultimate Load is 5 times the Working Load Limit.