

**LIGHT & SUPER CHAMPION DOUBLE SHEAVE**



**408 & 432**  
With Hook

- Light champion snatch block as a double sheave block.
- Drop forged swivel hook or swivel shackle.
- Can be furnished with bronze bushings or roller bearings.
- Opening feature permits easy insertion of Wireline in both sheaves with removal of one bolt.
- 408 and 409 can be furnished with S-4320 hook latch.
- 432 and 433 can be furnished with SS-4055 hook latch.
- Pressure lube fittings.
- 4-1/2" - 10" models furnished with dual rated Wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.



**409 & 433**  
With Shackle

*Fatigue Rated*



**408 / 409 Light Champion Double Sheave**

Sheave Diameter (in.)	Bearing Code	Stock No.		Wireline Size (in.) ‡	Working Load Limit (t)*	Weight Each (lbs.)		Rep. Sheave Stock No.	Rep. Latch Stock No.
		408 with Hook	409 with Shackle			408 with Hook	409 with Shackle		
† 4-1/2	BB	104023	105022	3/8 - 1/2	4	18	18	2000232	1096468
6	BB	104103	105102	5/8 - 3/4	12	45	50	460815	1096609
6	RB	104121	105120	5/8 - 3/4	12	45	50	472688	1096609
8	BB	104185	105184	5/8 - 3/4	12	53	58	461164	1096609
8	RB	104201	105200	5/8 - 3/4	12	53	58	473277	1096609
10	BB	104265	105264	5/8 - 3/4	12	70	75	461805	1096609
10	RB	104283	105282	5/8 - 3/4	12	70	75	473776	1096609
12	BB	194578	195185	5/8	12	90	95	462270	1096609
12	RB	168044	195229	5/8	12	90	95	474141	1096609
12	BB	104345	105344	3/4	12	90	95	462289	1096609
12	RB	104363	105362	3/4	12	90	95	474150	1096609
14	BB	194621	195247	5/8	12	100	105	463625	1096609
14	RB	194649	195265	5/8	12	100	105	474766	1096609
14	BB	104425	105424	3/4	12	100	105	463634	1096609
14	RB	104443	105442	3/4	12	100	105	474775	1096609

\* Ultimate Load is 4 times the Working Load Limit. † Available in Bronze Bushed only. ‡ May be furnished in other Wireline sizes.

**432 / 433 Super Champion Double Sheave**

Sheave Diameter (in.)	Bearing Code	Stock No.		Wireline Size (in.) ‡	Working Load Limit (t)*	Weight Each (lbs.)		Sheave Diameter (in.)	Bearing Code	Stock No.		Wireline Size (in.) ‡	Working Load Limit (t)*	Weight Each (lbs.)	
		432 with Hook	433 with Shackle			432 with Hook	433 with Shackle			432 with Hook	433 with Shackle				
8	BB RB	209624 209642	209811 209839	1	20	105	117	12	BB RB	209722 209740	209919 209937	1	20	140	152
8	BB RB	122021 122049	123020 123048	1 1/8	20	105	117	12	BB RB	122021 122049	123173 123191	1 1/8	20	140	152
10	BB RB	209660 209697	209857 209884	1	20	122	134	14	BB RB	209660 209697	209955 209973	1	20	190	202
10	BB RB	122094 122110	123093 123119	1 1/8	20	122	134	14	BB RB	122094 122110	123253 123271	1 1/8	20	190	202

\* Ultimate Load is 4 times the Working Load Limit. † Available in Bronze Bushed only. ‡ May be furnished in other Wireline sizes.



**NOTE:** When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and Wireline size.