



HEAVY DUTY SNATCH BLOCKS



L-5-H



L-5-S



L-5-T

- Hook is Forged Alloy Steel – Quenched and Tempered.
- Shackle is Forged Alloy Steel – Quenched and Tempered.
- Designed for fast, efficient line changes.
- All parts are forged.
- Beaded side plate prevents rope from jamming.
- Available with hook, shackle or tail board (pin only).
- Can be furnished with hook latch.
- Blocks furnished with dual rated Wireline sheaves.
- Fatigue Rated.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.



Fatigue Rated



L-160 Series Heavy Duty Snatch Blocks

Block No.	Bearing Code	L-160 Stock No.	Fitting	Sheave Diam. (in.)	Working Load Limit (t)*	Wireline Size (in.)	Weight Each (lbs.)	Rep Sheave Stock No.	Rep. Latch Stock No.
L-5-H	BB	599506	Hook	5	6	3/8 - 1/2	15	592095	1096468
L-5-H	RB	599515	Hook	5	6	3/8 - 1/2	15	592157	1096468
L-5-S	BB	599524	Shackle	5	6	3/8 - 1/2	15	592095	-
L-5-S	RB	599533	Shackle	5	6	3/8 - 1/2	15	592157	-
L-5-T	BB	599542	Tailboard	5	6	3/8 - 1/2	10	592095	-
L-5-T	RB	599551	Tailboard	5	6	3/8 - 1/2	10	592157	-
L-6-H	BB	599560	Hook	5-7/8	12	5/8 - 3/4	32	592175	1096609
L-6-H	RB	599579	Hook	5-7/8	12	5/8 - 3/4	32	592255	1096609
L-6-S	BB	599588	Shackle	5-7/8	12	5/8 - 3/4	30	592175	-
L-6-S	RB	599597	Shackle	5-7/8	12	5/8 - 3/4	30	592255	-
L-6-T	BB	599604	Tailboard	5-7/8	12	5/8 - 3/4	18	592175	-
L-6-T	RB	599613	Tailboard	5-7/8	12	5/8 - 3/4	18	592255	-

* Ultimate Load is 4 times the Working Load Limit.



NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and Wireline size.
NOTE: Tail Board does not contain the spool that is required with the hook (L-5-H) and shackle (L-5-S) snatch blocks.