

GENERAL PURPOSE SNATCH BLOCKS



L-45-H



L-45-S



L-45-T

- Hook is Forged Alloy Steel – Quenched and Tempered.
- Shackle is Forged Alloy Steel – Quenched and Tempered.
- All parts are forged.
- Opened and closed in seconds without the use of tools.
- Available with hook, shackle or tail board (pin only).
- Either wire or manila rope may be used.
- Can be furnished with hook latch.
- Blocks furnished with dual rated Wireline sheaves.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.



L-170 Series General Purpose Snatch Blocks

Block No.	Bearing Code	L-170 Stock No.	Fitting	Sheave Diam. (in.)	Working Load Limit (t)*	Wireline Size (in.)	Manila Rope Size (in.)	Weight Each (lbs.)	Rep Sheave Stock No.	Rep. Latch Stock No.
L-45-H	BB	599800	Hook	4-1/8	5	3-8 - 1/2	1-1/4	13	460405	1096468
L-45-H	RB	599819	Hook	4-1/8	5	3/8 - 1/2	1-1/4	13	472580	1096468
L-45-S	BB	599828	Shackle	4-1/8	5	3/8 - 1/2	1-1/4	13	460405	-
L-45-S	RB	599837	Shackle	4-1/8	5	3/8 - 1/2	1-1/4	13	472580	-
L-45-T	BB	599846	Tail Board	4-1/8	5	3/8 - 1/2	1-1/4	9	460405	-
L-45-T	RB	599855	Tail Board	4-1/8	5	3/8 - 1/2	1-1/4	9	472580	-

* Ultimate Load is 4 times the Working Load Limit.



NOTE: When Ordering, specify either roller bearing or bronze bushed sheaves.
NOTE: Tail board does not contain the spool that is required with the hook (L-45-H) and shackle (L-45-S) snatch blocks.