

Western Blocks for Manila Rope



T-350-C
Gin Block

Gin Blocks for Manila Rope

- For light hoisting by Roofers and Contractors.
- Furnished with drop forged swivel latch hooks.

350C, 350B, 350R

Block Size (in.)	Fitting	Gin Block Stock No.			Sheave Size (in.)			Manila Rope Size (in.)	Working Load Limit (lbs.)*	Weight Each (lbs.)
		T-350-B	T-350-R	T-350-C	Outside Diam.	Rim Thickness	Bearing Diam.			
8	T	710403	710207	710001	8.00	1.25	.75	7/8	1000	9.0
10	T	710421	710225	710029	10.00	1.25	.88	1	1000	9.8
12	T	710449	710243	710047	12.00	1.38	.88	1	1000	12.7

*Ultimate Load is 3 times the Working Load Limit.

Bearing Code : B - Self Lubricating Bronze Bushed; R - Roller Bearing; C - Common Iron
Fitting Type : T - Swivel Latch Hook



HS-130-B
Single

Painter's Supply Blocks for Manila Rope

- Furnished in Bronze Bushed.
- For 3/4" Manila Rope.
- Steel Parts are Galvanized.
- Furnished with Loose Side Hooks with Latch or Shackle.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26.

HS-130B, HS-135B, P-135B

Block Size (in.)	Fitting	Single Sheave Blocks	Double Sheave Blocks	
		HS-130 B* Stock No.	HS-135 B* Stock No.	P-135 B* Stock No.
6	HS	601236	631034	-
6	HS	-	-	8004829

*Bearing Code : B - Self Lubricating Bronze Bushed
Fitting Type : HS - Latch Hook, P= Screw pin anchor shackle.

HS-130B, HS-135B, P-135B

Block Size (in.)	Sheave Size (in.)			Manila Rope Size (in.)	Resultant Working Load Limit (lbs.)*		Weight Each (lbs.)	
	Outside Diam.	Rim Thickness	Center Pin Dia.		130 Single	135 Double	130 Single	135 Double
6	3.50	1.00	.75	3/4	1800	2500	5	10

*Ultimate Load is 4 times the Resultant Working Load Limit.