




IPBUZ

The IPBUZ shipbuilding clamps are used for lifting, transferring and placing bulb profiles onto ship's hulls perpendicularly. These clamps are fitted with a locking device for both open and closed positions, which ensures complete reliability. They are to be used exclusively for bulb profiles (not for plates).

For Lifting, Transferring and Placing Bulb Profiles onto Ship's Hulls Perpendicularly

- Available in capacities of .75 thru 3.75 metric tons.
- Jaw openings available: HP 4.75" to HP 17.00".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Company name (CrosbyIP), logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. User manual with test certificate is included with each clamp.
- Optional IP-5000 Stinger assembly available (see page 428). Allows for easy connection between the clamp and hoist hook.
- Maintenance replacement parts are available.
- Manufactured by an ISO 9001 facility.
- All sizes are **RFID EQUIPPED**.



Model IPBUUZ: with Universal Hoisting Eye Model IPBUZ: with Fixed Hoisting Eye

Model	Working Load Limit (t)*	Stock No.	Weight Each (lbs.)	Dimensions (in.)								
				Profile A †	B	C	D	E	F	G	H	K
IPBUUZ	.75	2705601	18.7	HP 4.75-7.88	3.35	8.90	15.35	2.76	8.27	2.40	2.76	.63
With fixed hoisting eye												
IPBUZ	.75	2705600	15.4	HP 4.75-7.88	3.35	8.90	15.35	2.76	8.27	2.40	2.76	.63
IPBUZ	1.5	2705701	33.1	HP 8.63-17.00	7.72	15.63	22.36	2.76	10.08	2.72	1.89	.63
IPBUZ	3.75	2705702	62.9	HP 8.63-17.00	9.37	17.24	22.24	3.15	13.98	2.52	3.94	.79

* Design Factor based on EN 13155 and ASME B30.20. † Profile A is the type of Holland Bulb (HP) style and size material.

