## PREECEMAY

## FLUX CORED WIRE - ABRALLOY

**ABRALLOY** flux cored wires are available in a range of sizes, with specifications to suit all applications. Welding using wire is faster than using conventional stick electrodes due to the higher currents that can be used, therefore increasing productivity on site.

All our wires are open arc, which give greater deposition rates when welding in air rather than using a gas shield. Open arc welding does not require any separate flux and only a standard power source and wire feed unit are required. All the deposits can only be machined by grinding.

COMPARATIVE WELD METAL DEPOSITION DATA										
PROCESS	SIZE MM	AMPS	VOLTS	KG/HR	ALLOY YIELD %					
STANDARD EXTRUDED ELECTRODE	4	180	24	1.62	46.80					
STANDARD EXTRODED ELECTRODE	5	250	25	2.01	46.80					
HIGH RECOVERY EXTRUDED ELECTRODE	4	240	25	2.25	60.00					
HIGH RECOVERY EXTRODED ELECTRODE	5	350	26	3.50	60.00					
SOLID WIRE	1.2	150-300	25-30	2.20	55.00					
	1.6	200-390	25-33	3.00	55.00					
	1.6	150-300	25-29	3.60	60.00					
FLUX CORED WIRE	2.4	250-400	26-31	4.50	65.00					
	2.8	270-450	26-31	5.50	65.50					
	3.2	300-500	26-31	6.80	69.00					







FLUX CORED WIRE																	
GRADE		DIAMET	WELD METAL ANALYSIS %														
	1.6	2.0	2.4	2.8	с	Cr	Si	Mn	в	Mo	Nb	v	w	HRC	APPLICATIONS		
AW10			~	~	3.5	3.5	0.3	0.4					49.0	65	- Fans - Pump impellors	- Pug mills - Augers	- Feed screws - Dredger cutters
AW23			~	~	5.3	22.0	1.0	1.3		6.0	6.5		2.0	65	- Screens - Rotating chutes	- Throat armour in blast furnaces	- Cement kilns - Sinter prongs
AW31	~	~	~	~	5.0	25.5	1.0	1.1						58	- Crusher rollers - Table liners	- Mantels - Slurry pipes	- Crusher cones - Dredge pump bodies
AW31S	~	~	~	~	5.0	30.0	0.8	1.5	0.6					62			
AW31WP	~	~	~	~	5.4	28.3	1.2	0.4						58	As above plus chromium carbide plate manufacturers. Used extensively in fabrications.		
AW37	~	~	~	~	5.0	21.5	0.8	1.5			6.3			60 / 64	- Wing hammers - Shovel teeth	- Mixer blades - Crusher jaws	- Breaker bars
AW58	~	~	~	~	5.0	15.5	1.0	1.1						58/60	- Crusher parts - Conveyor screws	- Augers - Bucket lips	- Agricultural parts
AW60	~	~	~	~	0.6	6.3	0.7	1.8				0.8		55 / 60	- Cutting edges - Drive tumblers	- Shovel undersides - Bucket teeth / lips	<ul> <li>Road construction equipment</li> </ul>
AW108	~	~	~	~	0.4	14.1	0.7	14.0						22/30	- Crusher hammers - Rail points	- Crusher jaws - Bucket teeth	- Wear plate edges

## PREECEMAY FZE

PO Box 326690, Ras Al Khaimah Free Trade Zone, Island Street Ras Al Khaimah, United Arab Emirates T: +971 (0)7233 4614

www.preecemay.com