



# AA Thread Seal Tape, Inc.

PTFE Thread Seal Tapes | PTFE Universal Joint Sealants

Polyethylene Encasements for Ductile Iron Pipe

PVC Pipe Wrapping Tapes | Industrial Tapes & Supplies

SINCE  
1979

## High Density Pink Plumbers Thread Seal Tape – Made in China

### Specifications

**Application:** This specification applies to expanded, 0.9 density x .004 Pink PTFE Thread Seal Tape supplied on finished spools.

**Composition:** Min. 99% virgin PTFE, Max. 1% pigment

**General Appearance:**

The tape appears pale pink in color. It shall be free of visible voids, cracks, folds, contamination, and have consistent physical properties.

**Physical Properties:**

Technical Performance	Tolerance	Method	Units
Width	+.03125	N/A	Inches
Length	260' +5%	N/A	Inches
Thickness	.0040 + .0005/-0	ASTM D374-42-A	Inches
Density	.90 + .1/-0	ASTM D792	g/cm <sup>3</sup>
Tensile-Longitudinal	3,000 max.	ASTM D882 (mod)	PSI
Elongation	50% min.	ASTM D882 (mod)	%

**Packaging:**

The 0.9 density expanded PTFE Thread Seal Tapes are wound on 1-inch ID plastic spools unless otherwise specified. Bulk packaging is sufficient to prevent damage during shipment.

**Useful Temperature Range:** -450°F to +500°F

**Reactivity:** Chemically inert to virtually all environments

**Flammability:** Non-flammable

**Storage:** Unlimited shelf life. (Less than 70°F recommended)