



AA Thread Seal Tape, Inc.

PTFE Thread Seal Tapes | PTFE Universal Joint Sealants

Polyethylene Encasements for Ductile Iron Pipe

PVC Pipe Wrapping Tapes | Industrial Tapes & Supplies

SINCE
1979

High Density Yellow Gas Line Thread Seal Tape Made in Italy

Specifications

Application: This specification applies to pigmented thread seal tape manufactured from Dupont Teflon. High Density Yellow Gas Line Thread Seal Tape is recommended for use on most threaded connections of pressurized gas systems including ethane, butane, and propane. This product may also be used on pressurized liquid systems.

Physical Properties

Compositions: Min. 99% virgin PTFE, Max. 1% pigment

Thickness: 0.0035 to 0.0040 IN

Tensile Strength: 2,000-PSI minimum

Elongation: 100% Nominal

Temp. Range: -450°F to +500°F

Pressure Rating: up to 10,000-PSI

Reactivity: Chemically inert to virtually all environments

Flammability: Non-Flammable

Shelf Life: Unlimited

Approvals: U/L Listed, tested to 300 PSIG with a minimum of 2 full wraps, U/L file No. MH26734, Seal material 19BN

High Density Thread Seal Tape meets or exceeds all requirements of MIL T-27730A.