



SPECIFICATION SHEET

Main Office & Warehouse:

1275 Kyle Ct. Wauconda, IL 60084

Western Warehouse:

4000 East. US-6, Spanish Fork, UT 84660

Yellow Gas Line Thread Seal Tape

Made in USA

Grade: PREMIUM FULL

Part # # 13031-13101

Specifications

Application: This specification applies to expanded, 0.9 density x 0.004" Yellow PTFE Thread Seal Tape supplied on finished spools.

Product Specifications

Chemical Properties:	Min. 99% virgin PTFE, Max. 1% pigment
Thickness:	See chart below
Density:	PREMIUM FULL
Elongation:	50% min. ASTM M882 (mod)
Pressure Rating:	10,000 max PSI
Tensile Strength:	1200-PSI minimum
Temp. Range:	-450F to +500F
Storage:	Unlimited shelf life (less than 70°F recommended)
Reactivity:	Chemically inert to virtually all environments
Flammability:	Non-flammable

Full Density Thread Seal Tape meets or exceeds all requirements of MIL T-27730A, UL Approved

Grade Scale	Standard	Medium	High	Full	Premium Full
Thickness (MIL)	0.3-3.5	3.0-3.5	3.4-4.0	3.5-4.0	3.5-4.0
Density (g/cm³)	0.3-0.7	0.7-0.8	0.8-0.9	0.9-1.5	1.5-1.6