2018





- · Powerful fuel-injected, 4-stroke engine is easy on gas
- Durable manual transmission with semi-automatic clutch
- Select 2WD or 4WD via a handlebar-mounted lever
- Large fuel tank & plush seat deliver extended, comfortable riding range
- · Rugged bodywork and full racks to tackle any task







Flame Red

Terra Green

2018





In 1983, Suzuki introduced the world's first 4-wheel ATV. Today, Suzuki ATVs are everywhere. From the most remote areas to the most everyday tasks, you'll find the KingQuad powering a rider onward. Across the board, our KingQuad lineup is an exceptional group of ATVs.

The 2018 Suzuki KingQuad 400FSi features a 5-speed manual-shift transmission and semi-automatic clutch for those who favor a bit sportier performance. It cranks out an impressive amount of torque and has an incredibly wide powerband for exceptional performance on the trail or on the job. A high-performance iridium spark plug and refined Pulsed-secondary AIR-injection (PAIR) system help provide outstanding fuel efficiency, clean emissions, and great performance.

KINGQUAD 400FSi FEATURES

ENGINE FEATURES

- The KingQuad 400FSi's fuel-injected 376cc 4-stroke, 4-valve engine produces efficient power and drivablity.
- Suzuki's class-leading fuel injection smooths power output, especially in the mid-to-high range, and provides excellent cold starting. The system uses 3D maps for optimum ignition, creating responsive yet environmentally compliant performance.
- Suzuki Advanced Cooling System (SACS) uses an oil cooler and thermostatcontrolled cooling fan to shed engine heat during hard work or cargo hauling.
- Push-button electric starting has a start-in-gear function when the rear brake is applied – allowing starting without shifting to neutral (as conditions permit).
- The Engine Control Unit (ECU) has slip control logic, which adjusts fuel injector duration and timing to improve drivability and grip in loose/slippery conditions.
- Highly efficient iridium spark plug contributes to better combustion, cleaner emissions, and longer plug life. Engine starting under low temperature is also improved.
- Pulsed-secondary AIR-injection (PAIR) system and catalyst-equipped exhaust system help the ATV meet emission standards while maintaining a high level of performance.

TRANSMISSION FEATURES

- 5-speed transmission with semi-automatic clutch with reverse allows the rider to select the ideal gear for maximum traction and fuel efficiency.
- Select 2- or 4-wheel drive with the flip of a handlebar-mounted lever. The shaft drive system is reliable, durable, and nearly maintenance-free.
- Torque-sensing limited-slip front differential provides maximum traction and light steering when in 4WD mode.
- · High-low selectable sub-transmission provides wide-ranging versatility.
- Automotive gate-type gearshift lever lets you conveniently choose high- or lowrange, neutral, or reverse.
- The ECU has a Reverse Mode that monitors vehicle speed so higher engine RPM can be used when getting out of mud or loose soil in reverse mode.

CHASSIS FEATURES

- · Sporty bodywork features sharply angled, high-clearance fenders.
- Suzuki's exclusive T-shaped seat delivers rider mobility during sport riding or tackling difficult terrain. It's also plush for extended riding comfort.
- Overall length is under 82 inches (208 cm) so the KingQuad fits into a 6.5-foot truck bed for easy transportation.
- Independent front A-arm suspension offers smooth performance and remarkable ground clearance with 6.7 inches (170.1 mm) of wheel travel.
- A swingarm rear-suspension with 6.7 inches (170.1 mm) of wheel travel and twin shock absorbers provide agile handling and plush ride.
- Dual front hydraulic disc brakes feature calipers with large 34 mm pistons and wide brake-pad surface area for increased stopping power and outstanding durability.
- Large, 25-inch CARLISLE tires with aggressive tread offer consistent traction in wet conditions yet have a quiet, smooth ride on hard-packed trails.
- Lightweight and strong plastic skid plates are sturdy to withstand trail pounding yet slippery enough to let obstacles slide below.

UTILITY/CONVENIENCE FEATURES

- Dual 35W headlights (with high and low settings) are part of the distinctive KingQuad grille appearance. Bright taillight helps make the ATV visible in dark conditions.
- Heavy-duty front and rear cargo racks let you take advantage of the ATV's superb load capabilities. Wrinkle paint finish on the racks and front bumper is durable and scratch resistance.
- LCD instrumentation includes speedometer, odometer, trip meter, hour meter, clock, fuel gauge, and indicators for reverse, neutral, oil, and FI.
- · Automotive-style DC power outlet on front fender.
- · Winch-ready mounts and wire conduit make winch installation simple.
- · Large 4.2-gallon (15.9 L) fuel tank provides outstanding riding range.
- · Full floorboards with integrated raised footpegs provide protection.
- A variety of Suzuki Genuine Accessories are available, including winches, windshield, front and rear bumpers, snow plow, aluminum skid pans, rack extensions, utility box, and more.
- 12-month limited warranty
- · For more details, please visit www.suzukicycles.com.

2018





KINGQUAD 400FSi SPECS

Engine:	4-stroke, air-cooled with SCAS, OHC single cylinder
Displacement:	376cc (22.94 cubic in.)
Bore x Stroke:	82.0 x 71.2 mm (3.228 x 2.803 in.)
Compression Ratio:	9.0: 1
Fuel System:	Suzuki electronic fuel injection
Starter:	Electric
Lubrication:	Wet sump
Transmission:	5-speed forward constant mesh, with high/low range
	and reverse
Clutch:	Dry shoe, automatic, centrifugal type
Driven Wheels:	2WD & 4WD
Final Drive:	Shaft drive
Suspension, Front:	Independent, double wishbone, coil spring, oil damped
Suspension, Rear:	Swingarm type, coil spring, oil damped
Brakes, Front:	Disc brakes, twin rotors
Dualina Danii	·
Brakes, Rear:	Single drum brake

Tire, Front:	AT25 x 8-12, tubeless type x 2
Tire, Rear:	AT25 x 10-12, tubeless type x 2
Fuel Tank Capacity:	4.2 US gal. (16.0 L)
Ignition:	Electronic ignition (transistorized)
Headlight:	12V 35/35W (HS1) x 2
Taillight:	12V 21/5W
Overall Length:	81.1 in. (2060 mm)
Overall Width:	45.1 in. (1145 mm)
Overall Height:	48.0 in. (1220 mm)
Wheelbase:	50.0 in. (1270 mm)
Ground Clearance:	9.8 in. (250 mm)
Seat Height:	33.1 in. (840 mm)
Curb Mass:	615 lbs. (279 kg.)