





# D4 (GGD35) Grease Guardian Standard Specification


4" INLET  
4" OUTLET



FRONT VIEW



END VIEW



TOP VIEW

## GREASE GUARDIAN STANDARD FEATURES:

- 3 Year Guarantee
- Fully Automatic Grease Removal Unit (AGRU)
- 16 gauge stainless steel welded tank
- Fully sealed air tight lid
- Left Hand / Right Hand Options
- PLC/HMI automatic controller
- Audible alerts
- Energy saving mode
- Long life skimmer blade
- Removable basket solids strainer
- Grease Guardian World asset management

## TECHNICAL DATA


Weight \_\_\_\_\_ 80 pounds  
 Material \_\_\_\_\_ 16 Gauge Stainless Steel  
 Interior \_\_\_\_\_ Stainless Steel & Acetal Plastic Components  
 Maximum Flow Rate \_\_\_\_\_ 35 gallons per minute  
 No of Skimming Wheels \_\_\_\_\_ 1  
 Solids Strainer Capacity \_\_\_\_\_ 8 Pounds  
 Skimming Rate \_\_\_\_\_ 11 pounds per hour  
 Programming/Control \_\_\_\_\_ 7 day, 24hr Multifunctional  
 Electrical Load \_\_\_\_\_ 110VAC 625watts 5.7A

## KEY INSTALLATION NOTES:

- Allow for the minimum clearances shown
- For tank base allow at least 46" length x 24.5" width clearance.
- Allow adequate access to slide-in strainer & slide-in grease collector from front.
- Inlet port is both single/dual entry
- Outlet port is both single/dual entry.
- Keep outlet piping at 1/8" per foot fall or more.
- User rubber adjustable pipe connectors as supplied.
- Only switch on after filling system with water to static level.
- Refer to long manual for full installation.

## Pre start up checks:

- Ensure unit is positioned on a level surface and is plumbed in securely.
- Ensure electrical outlet is fitted with dedicated ground fault circuit breaker.
- Ensure that the unit is filled with water to the correct level
- Ensure strainer basket is fully closed
- Set controller date and time as detailed in the manual
- Ensure that collection receptacle empty and securely in place



MINIMUM FLOOR SPACE RECOMMENDATION

## Specification

Install \_\_\_ Grease Guardian Model GGD35, self cleaning automatic grease removal unit, 16 gauge fully welded 304 stainless steel tank, stainless steel internal baffle plate, fully sealed air tight stainless steel lid and robust stainless steel clamps, stainless steel vertical lift solids strainer basket, left to right or right to left available with easy fit pipe couplings, 35 gallons per minute flowrate, and skimming rate of 11 pounds per hour. The GGD is supplied with stainless steel rotating grease skimming wheel, integral gas trap, totally enclosed geared drive unit, 600 watt immersion heater with self regulating safety control, programmable controller with interface, energy saving mode and audible alerts. The GGD is suitable for floor and shelf type mounting. 3 year warranty is standard.

### Electrical Details

GGD35 110vac, 625watts, 5.7A

## Grease Guardian World

Grease Guardian World is an interactive online register of all Grease Guardian branded products uploaded and managed by Grease Guardian, distributors and end users.

Grease Guardian World allows us to:

- Upload and manage individual sites
- Monitor specification, service history, supplier details for each Grease Guardian installed
- Upload and view installation photographs
- Upload and view Operation & Maintenance manuals
- Upload and view service engineer reports
- Locate sites using Google Maps linking
- Automatically remind distributors, customers and end users when service is due and warranties expire.
- Access and manage accounts on-line
- Manage recycled FOG

