

**JTC-3101 MINI AIR DIE GRINDER**

- Free speed: 25000 rpm
- Collet size: 6mm (1/4")
- Air inlet: 1/4"
- Air pressure: 90psi
- Air consumption: 300 L / min
- Net weight: 0.4kg
- Overall length: 140mm
- Exhaust system: Rear

**JTC-3321 SPOT WELD CUTTER KIT**

- Quick drills out spot weld on fenders, doors, etc.
- Retractable guide pin assures accurate cut.
- Double edged cutting blade assures long using life.
- 500rpm working and 1/4" arbors.
- Contents:
3/8" spot weld cutter x 1 pc; 3/8" spot weld bladex 2 pcs
5/16" spot weld cutter x 1 pc; 5/16" spot weld bladex 2 pcs
Tip for spot weld cutter x 2 pcs; hex wrench x 1 pc

**JTC-3401 1/2" HEAVY DUTY AIR MINI IMPACT WRENCH**

- Free speed: 11000rpm
- Bolt capacity: 5/8"
- Air inlet: 1/4"
- Air pressure: 90~120 psi
- Max torque: 400 ft. /lb.
- Weight: 1.5kgs
- Overall length: 142mm

**JTC AUTO TOOLS USA**

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-3404 1/4" 90° AIR PALM RATCHET WRENCH

- Free speed: 250rpm
- Max torque: 35Nm
- Air inlet: 1/4"
- Air pressure: 90psi
- Weight: 0.45kgs
- Overall length: 125mm
- Exhaust system: Rear



JTC-3745 SAW BLADES – 32T

- Spec: 32T x 12" (bi-metal)



JTC-3747 WIDE TYPE SAW BLADES – 9" x 18T

- Made from bi-metal for not easy broken.
- Suitable for electric and air saw JTC-5052 and JTC-5236.
- Width: 29mm
- thickness: 1.5 ~ 3mm
- Size: 9" x 18T
- Teeth Length: 210mm



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-3748 WIDE TYPE SAW BLADES – 12" x 14T

- Made from bi-metal for not easy broken.
- Suitable for electric and air saw JTC-5052 and JTC-5236.
- Width: 29mm; thickness: 1.5~3mm
- Size: 12"x14T
- Teeth Length: 280mm



JTC-3822 AIR DIE GRINDER

- Free speed: 22000 rpm
- Collet size: 6mm (1/4")
- Air inlet: 1/4"
- Air pressure: 90psi
- Air consumption: 350 L / min
- Net weight: 0.6kg
- Overall length: 175mm
- Exhaust system: Rear



JTC-3824 AIR SANDER

- Pad size: Diameter: 3", 4-1/2", 5"
- Free speed: 16000rpm
- Air inlet: 1/4"
- Air pressure: 90psi
- Air consumption: 350 L / min
- Net weight: 1.2kg
- Length x height: 140 x 160mm
- Exhaust system: Rear



#3733 OPTIONAL



JTC AUTO TOOLS USA

678 - 876 - 3470
 2600 NORTHLAKE DR., SUITE F,
 SUWANEE, GA, 30024



JTC-3834 1/2" ULTRA DUTY COMPOSITE AIR IMPACT WRENCH (1100LB)

- Designed for repair work with the possibility of using a shock mechanism.
- Max Torque: over 1,100 ft-lb (1,486 Nm).
- Working Torque: 250 ~ 600 ft-lb (338 ~ 810 Nm).
- Blow per Min.: 1250rpm
- No-load speed: 8,000 RPM +/- 10%.
- Recommend air pressure: 90 PSI (6.35 kgs).
- Air Inlet: 1/4" PT.
- Min. Hose Size: 3/8" (10 mm) I.D.
- Overall Length: 7.3" (186 mm).
- Weight: 4.4 LBS (2 kgs).



JTC-3835 1/2"DR. HI-TORQUE ANGLE HEAD AIR IMPACT WRENCH

- Max. Torque: 200 ft.-lbs. (271Nm) in reverse.
- Working Torque : 45 ~ 160 ft-lb (61~217 Nm)
- Impact per Min.: 2,100rpm
- No-load speed: 6000 RPM +/-10%
- Recommend air pressure: 90 PSI (6.35 kgs)
- Air Inlet: 1/4" NPT (PT)
- Min. Hose Size: 3/8" (10 MM) I.D.
- Overall Length: 13.1" (332 MM)
- Weight: 4.3 LBS (1.98 KGS)



JTC-3837 TWO WAY ANGLE AIR DRILL

- Chuck size: 10 mm (3/8").
- Free Speed: 1600 R.P.M.
- Net Weight: 1.1 KG.
- Air inlet: 1/4".
- Length x Height: 210 x 110 mm.
- Air Consumption: 300L/min.
- Exhaust System: Rear.
- Air Pressure: 90 psi.



JTC AUTO TOOLS USA


678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-3929 1/4" STUBBY AIR RATCHET WRENCH

- Free speed: 230 rpm
- Max torque: 50Nm
- Air inlet: 1/4"
- Air pressure: 90psi
- Air consumption: 130 L/min
- Net weight: 0.5kgs
- Overall length: 165mm
- Exhaust system: Rear



JTC-4428 BALL JOINT TOOL FOR AIR HAMMER

- Use for removing and installing the tie rod ball joint.
- Replaceable head size; specially designed main rod, can reach into tight space.
- Must use with JTC-3309 or JTC-3310.



JTC-5114 1/4" HEAVY DUTY AIR RIVETER

- Stroke: 19mm.
- Capacity:
Aluminum rivet: 2.4, 3.2, 4.0, 4.8, 6.4.
Stainless rivet: 2.4, 3.2, 4.0, 4.8.
- Size: 260 x 90 x 325 mm.
- Weight: 2.07kgs.
- Air inlet: 1/4"PT.
- Air consumption: 4.2 C.F.M



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-5212 1/2" AIR IMPACT WRENCH (1000LB)

- Free speed: 7200 rpm.
- Bolt capacity: 29 mm.
- Air Inlet: 1/4"
- Air pressure: 90~120 psi.
- Max torque: 1000 ft. / lb.
- Weight: 2.6 kgs.
- Overall length: 171 mm

**MAX
1000ft/lb**



JTC-5223 1" LONG ANVIL AIR IMPACT WRENCH (LIGHT WEIGHT)

- Bolt capacity: 2" (50mm)
- Max torque: 2500ft. /lb. (3390NM)
- Free speed: 4800 rpm
- Air consumption: 16 cfm
- Air inlet: 1/2"
- Air pressure: 90psi
- Overall length: 570mm
- Net weight: 11.9 kgs
- Anvil length: 8"
- Clutch mechanism: Twin Hammer



JTC-5301 1/2" MINI AIR IMPACT WRENCH

- Max torque: 550 ft/lb.
- Net weight: 1.36 kg.
- Length: 99 mm.
- Air Consumption: 0.2 m³/min.
- Air Inlet: 1/4" inch.
- Vibration: 2.8 m/g².
- Speed: 11,000 RPM.
- Mechanism: jumbo hammer.



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-5306 3/8" MINI AIR IMPACT WRENCH

- Max torque: 500 ft. /lb. (678Nm).
- Net weight: 1.36 kg.
- Length: 99 mm.
- Air Consumption: 0.2 m³/min.
- Air Inlet: 1/4" inch.
- Vibration: 2.8 m/g²
- Speed: 11,000rpm
- Mechanism: jumbo hammer.



JTC-5421 1/2" IMPACT ADAPTER FOR AIR HAMMER

- Must use with air hammer, suggest to use with JTC-3309, 3310.
- Size: 1/2" DR., Length: 560mm.



JTC-5445 AIR HAMMER DERUSTING NEEDLES

- Must use with JTC-3309 or JTC-3310.
- Use for removing rust and dirt.
- Length: 226mm / Quality of needle: 19 pcs



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-5446 1" AIR IMPACT WRENCH

- Bolt capacity: 1-3/4" (45 mm)
- Max Torque: 2000 ft. /lb.(2711 Nm)
- Net weight: 5.5 kgs
- Length: 240mm
- Air consumption: 0.32 m³/min.
- Air inlet: 3/8"
- Vibration: 6.1 m/s²
- Speed: 4500 rpm
- Mechanism: twin hammer




JTC-5509 18V 3-IN-1 RECHARGEABLE SCREWDRIVER

- Can be used as an impact, drill or hammer drill driver.
- Built-in interchangeable carbon brush motor.
- Variable speed, reversible switch and electric brake.
- Light weight and handy design of housing, provide highly efficient ventilation.
- Slide release battery design with power indicator.
- Built-in LED light for working under low light environment.
- Contents:
2 pcs of 2.0Ah Li-ion battery (with charger)
50mmL Bits: PH1, PH2, S16
Drill Bits: Ø2, Ø3mm
- Voltage: DC 18V
- Unload speed: 0-2600 RPM
- Shaft: 1/4" HEX drive
- Max Torque: 120Nm / 1062 lbs
- Weight: 1200g



JTC-5510 18V 1/2" RECHARGEABLE IMPACT WRENCH

- Built-in interchangeable carbon brush motor.
- Variable speed, reversible switch and electric brake.
- Built-in LED light for working under low light environment.
- Contents:
Professional socket: 17, 19, 21mm.
4.0Ah Li-ion battery - 1 pc.
2.0Ah Li-ion battery - 1 pc.
- Battery charger.
- Voltage: DC 18V
- Unload speed: 0-2000 RPM
- Shaft: 1/2" Square drive
- Torque:
300Nm / 2655 lbs. (5 seconds - Forward mode)
500Nm / 4425 lbs. (10 seconds - Forward mode)
- Max torque: 850Nm / 7523 lbs. (Reverse mode)
- Weight: 2652g (with 4.0Ah battery)



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-5643 AIR CORNER DIE GRINDER

- Free speed: 14000rpm
- Air inlet: 1/4"
- Air pressure: 90psi
- Net weight: 1.1kgs
- Disc size: 4" x 1/16" x 3/8"
- Overall length: 360mm
- Tube length: 540mm



JTC-5719 3/8" HEAVY DUTY AIR RATCHET WRENCH

- With close captured ratchet housing, comfort grip and rear exhaust.
- Free speed: 240rpm
- Working torque: 40Nm
- Air inlet: 1/4"
- Air pressure: 90psi
- Weight: 0.8kgs
- Length: 180mm.
- Air consumption: 3.1cfm.



One body



JTC-5720 AIR NIBBLER & KNIFE

- Free speed: 3500rpm
- Width of cut: 4.5mm
- Air inlet: 1/4"
- Air pressure: 90psi
- Weight: 0.92kgs; Length: 190mm.
- Air consumption: 4cfm.
- Capacity: Iron: 2.0mm; stainless: 1.5mm



JTC AUTO TOOLS USA

678 - 876 - 3470
 2600 NORTHLAKE DR., SUITE F,
 SUWANEE, GA, 30024



JTC-5806 2" STRIPPING DISC WITH SHAFT

- Disc diameter: 2" inside thread.
- Length: 60 mm.
- Shaft : 6 mm



JTC-5812 1/2" HEAVY DUTY AIR IMPACT WRENCH (800LB)

- Free speed: 7500 rpm
- Bolt capacity: 27 mm
- Air Inlet: 1/4"
- Air pressure: 90~120 psi
- Max torque: 800 ft / lb
- Weight: 2.5 kgs
- Overall length: 164 mm



JTC-5813 1" AIR IMPACT WRENCH

- Bolt capacity: 2" (50mm)
- Max torque: 2500 ft. / lb. (3390N-M)
- Free speed: 3400 rpm
- Air consumption: 19.7 cfm
- Air inlet: 3/8"
- Air pressure: 90 psi
- Overall length: 302 mm
- Net weight: 11.8 kg
- Clutch mechanism: Twin Hammer



JTC AUTO TOOLS USA

678 - 876 - 3470
 2600 NORTHLAKE DR., SUITE F,
 SUWANEE, GA, 30024



JTC-5814 1" LONG ANVIL AIR IMPACT WRENCH

- Bolt capacity: 2" (50mm)
- Max torque: 2500 ft / lb (3390N-M)
- Free speed: 3700 rpm
- Air consumption: 20 cfm
- Air inlet: 1/2"
- Air pressure: 90 psi
- Overall length: 594 mm
- Net weight: 16.3 kg
- Anvil length: 8"
- Clutch mechanism : Pin-less



JTC-5815 ANGLE DIE GRINDER

- Free speed: 22000 rpm
- Collet size: 6mm (1/4")
- Air inlet: 1/4"
- Air consumption: 150 L/mm
- Net weight: 0.5kg
- Air Pressure: 6.3bar/90psi
- Length x Height : 144x75mm



JTC-5819 1/4" AIR RIVETER

- Stroke: 16mm
- Capacity: 2.4, 3.2, 4.0, 4.8, 6.4; Aluminum nails
- LxWxH: 170 x 77 x 277mm
- Weight: 1.52 kg
- Air inlet: 1/4" PT



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024

**JTC-5837 AIR METAL PUNCH FOLDER**

- Punch diameter: $\phi 5$ mm
- Max punch thickness: 2 mm
- Length: 250mm
- Weight: 1.28kg
- Air Inlet: 1/4" PT

**JTC-5901 1" LONG ANVIL AIR IMPACT WRENCH**

- Bolt capacity: 2" (50mm)
- Max torque: 2500 ft. /lb. (3390N-M)
- Free speed: 3700 rpm
- Air consumption: 20 cfm
- Air inlet: 1/2"
- Air pressure: 90 psi
- Overall length: 622 mm
- Net weight: 14.6 kg
- Anvil length: 8"
- Clutch mechanism: Twin Hammer

**JTC-5904 10M M AIR BELT SANDER**

- Sander: 10 x 330mm
- Weight: 0.75kg
- Length: 280mm
- Speed: 16000bpm
- Air inlet: 1/4" PT
- Hose size: 1/4"
- 1pc of each #80, #100, #120 belts are attached.

**JTC AUTO TOOLS USA**

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024



JTC-3310K 8 PCS AIR HAMMER SET

- Content:
 - 1 PC - JTC-3310 AIR HAMMER
 - 1 PC - JTC-3334 SAFTY COUPLER
 - 6 PCS - JTC-3326, 3327, 3330, 3331, 3332, 3333 CHISELS.



JTC-3320A AIR REVERSIBLE DRILL

- Free speed: 3000rpm
- Air inlet: 1/4"
- Air consumption: 280 L/mm
- Chuck size: 3/8" (10mm)
- Length x Height: 167 x 163mm
- Net weight: 1kg
- Air Pressure: 6.3bar/90psi



JTC-3825A LOW SPEED AIR SPOT DRILL

- Free Speed: 1100RPM±10%
- Air inlet: 1/4"
- Air Pressure: 90PSI
- Overall Length: 252mm
- Weight: 1.71kgs
- Drill Bit Size: 8mm x 44L(Tin Coating).



Optional kit: 3825A-K



JTC AUTO TOOLS USA
 678 - 876 - 3470
 2600 NORTHLAKE DR., SUITE F,
 SUWANEE, GA, 30024



JTC-3833P REPAIR KITS FOR JTC-3833, 3320A, 3837

- Repair kit for pneumatic drill JTC-3833.
- Overall dimensions:
60/40/40 mm. (L / W / H)
- Weight: 165g



JTC-3929P REPAIR KITS FOR JTC-3929, 3404

- Repair kit for pneumotrack JTC-3929.
- Overall dimensions: 80/60/10 mm. (L / W / H)
- Weight: 38g



JTC-5646A 4" AIR GRINDER

- Disc size: 4"
- Weight: 1.75kgs
- Free speed: 11000 rpm
- Length: 226mm
- Air inlet: 1/4"
- Air consumption: 0.12m³ /min
- Strengthened inlet, tool is firmer.



JTC AUTO TOOLS USA

678 - 876 - 3470

2600 NORTHLAKE DR., SUITE F,
SUWANEE, GA, 30024